



Have an unique ball locking with plastic jettling mechanism that allow easily and quickly installed and not undone

High tensile strength

Non-flammability

Operating temperature: -40°C-85°C

High resistance to acetic acid, alkali acid, sulphuric acid, corrode, etc

All length/ colour are available stainless steel 304#, 316#

Part No	Appox.Length mm(inch)	Appox.Width mm(inch)	Max.Bundle Dia mm(inch)	Min. Loop Tensile Strength N(lbs)
FZOSJ-13X200	200(7.87)	13(0.51)	50(1.97)	1200(270)
FZOSJ-13x250	250(9.84)		63(2.48)	
FZOSJ-13X300	300(11.8)		76(2.99)	
FZOSJ-13X350	350(13.78)		89(3.5)	
FZOSJ-13X400	400(15.75)		102(4.02)	
FZOSJ-13X450	450(17.72)		115(4.53)	
FZOSJ-13X500	500(19.69)		128(5.04)	
FZOSJ-13X550	550(21.65)		141(5.55)	
FZOSJ-13X600	600(23.62)		154(6.06)	
FZOSJ-13X650	650(25.59)		167(6.57)	
FZOSJ-13X700	700(27.56)		180(7.09)	
FZOSJ-16X200	200(7.87)	16(0.63)	50(1.97)	1500(337)
FZOSJ-16X250	250(9.84)		63(2.48)	
FZOSJ-16X300	300(11.8)		76(2.99)	
FZOSJ-16X350	350(13.78)		89(3.5)	
FZOSJ-16X400	400(15.75)		102(4.02)	
FZOSJ-16X450	450(17.72)		115(4.53)	
FZOSJ-16X500	500(19.69)		128(5.04)	
FZOSJ-16X550	550(21.65)		141(5.55)	
FZOSJ-16X600	600(23.62)		154(6.06)	
FZOSJ-16X650	650(25.59)		167(6.57)	
FZOSJ-16X700	700(27.56)		180(7.09)	