Cingo Transporter
Regulatory area: EE
M500



MODEL	M500
Height (mm)	1125
Rubber track dimension (mm)	160x72x33
Ground clearance (mm)	115
Width (mm)	690
Length (mm)	1471

MODEL	M500
PERFORMANCE	
Dumper capacity (m3)	0,23
Unladen weight (kg)	230
Maximum cross gradient (%)	20
Maximum longitudinal gradient (%)	35
Maximum load capacity (kg)	500
Maximum speed (km/h)	3,5
Implement pump	—
Implement pump delivery (l/min)	—
OPERATOR WORKSTATION	
Shock-absorbing Operator Platform	—
Lever controls	●
Engine status display	—
Operator support handle	●
ENGINE	
Electric Starter	—
Battery (Electric only)	—
Inverter (Electric only)	—
Fuel	Gas
Displacement/Cylinders (cc/n°)	196/1
Engine	Honda GX200
Engine Power (hp/kW)	5,6/4,1
Transmission type	Hydraulics
Track support rollers	3
Gear motors	—
Hydrostatic pump	—
Fuel tank capacity (l)	3,1
Hydraulic oil tank capacity (l)	21
Anti-pollution technology	Stage V
Cooling system	Air
OPTIONS	
Multifunctional accessory with quick-release coupling	—
Jump-start cable	—
Oil cooler	—
Drain line	—
3-point rear linkage	—
Quick boom coupling	—
Stabiliser leg	—

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer

MERLO S.P.A.
Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111
info@merlo.com www.merlo.com

Release 8/10/2026 - 11:42

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.