


High Capacity Telehandlers

Regulatory area: NA
TF65.9




MODEL	TF65.9T-170-HF	TF65.9TCS-170-HF	TF65.9TCS-170-CVT-HF
A - Length (in)	207	207	207
C - Wheelbase (in)	120	120	120
F - Ground clearance (in)	17	17	17
H - Width (in)	94	94	94
M - Cab width (in)	40	40	40
P - Height (in)	99	99	99
S - Fork steering range (in)	210	210	210

MODEL	TF65.9T-170-HF	TF65.9TCS-170-HF	TF65.9TCS-170-CVT-HF
PERFORMANCE			
Unladen weight (lb)	24250	24691	24801
Maximum load capacity (lb)	14300	14300	14300
Lift height (ft)	28'	28'	28'
Maximum reach (ft)	15'	15'	15'
Boom side-shift (in)	—	—	—
Frame levelling (%)	+/- 8	+/- 8	+/- 8
Boom section	2	2	2
POWERTRAIN			
Engine	FPT NEF45	FPT NEF45	FPT NEF45
Range/Cylinders (l)	4.5/4	4.5/4	4.5/4
Engine power (kW/HP)	125/170	125/170	125/170
Anti-pollution technology	Stage V - SCR + DOC + DPF	Stage V - SCR + DOC + DPF	Stage V - SCR + DOC + DPF
Reversible Fan	○	○	○
Maximum speed (mph)	25	25	25
Fuel tank capacity (gal)	37	37	37
AdBlue tank capacity (gal)	4.8	4.8	4.8
Hydrostatic transmission EPD	●	●	CVTTronic
Electronic joystick	STD	STD	STD
Axles	Axial	Axial	Axial
Brakes	Dry discs	Dry discs	Dry discs
HYDRAULIC			
Delivery / pressure (gal/min-psi)	42.3 - 3626	42.3 - 3626	42.3 - 3626
Hydraulic oil tank capacity (gal)	26.4	26.4	26.4
CAB			
ASCS	Full	Full	Full
FOPS/ROPS Cab	●	●	●
Tilting cab	—	—	—
CONFIGURATION			
Hydropneumatic Suspension CS Merlo	—	●	●
Hydropneumatic Suspension EAS Merlo	—	—	—
Permanent four-wheel drive	●	●	●
Three steering way	●	●	●
Standard tyres	500/70-24"	500/70-24"	500/70-24"
Hydraulically controlled stabilizers	—	—	—
Turret rotation	—	—	—
PTO (rpm)	—	—	—
3-point rear linkage (lb)	—	—	—

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer



MERLO S.P.A.

Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 21/11/2025 - 8:32

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.