# Cingo Transporter
## Regulatory area: AU
## M8.3TD-EVO




| MODEL | M8.3TDEVO |
|---|---|
| Height (mm) | 1175 |
| Rubber track dimension (mm) | 180x72x36 |
| Ground clearance (mm) | 100 |
| Width (mm) | 800 |
| Length (mm) | 1800 |

| MODEL | M8.3TDEVO |
|---|---|
| **PERFORMANCE** | |
| Dumper capacity (m3) | 0,33 |
| Unladen weight (kg) | 510 |
| Maximum cross gradient (%) | 20 |
| Maximum longitudinal gradient (%) | 35 |
| Maximum load capacity (kg) | 800 |
| Maximum speed (km/h) | 4 |
| Implement pump | 8+2,5 |
| Implement pump delivery (l/min) | 27+8 |
| **OPERATOR WORKSTATION** | |
| Shock-absorbing Operator Platform | ● |
| Lever controls | ● |
| Engine status display | ● |
| Operator support handle | ● |
| **ENGINE** | |
| Electric Starter | ● |
| Battery (Electric only) | – |
| Inverter (Electric only) | – |
| Fuel | Diesel |
| Displacement/Cylinders (cc/n°) | 600/2 |
| Engine | Kubota Z602 |
| Engine Power (hp/kW) | 17/12,5 |
| Transmission type | Hydrostatic |
| Track support rollers | 4 |
| Gear motors | ● |
| Hydrostatic pump | ● |
| Fuel tank capacity (l) | 14 |
| Hydraulic oil tank capacity (l) | 19 |
| Anti-pollution technology | Stage V |
| Cooling system | Liquid |
| **OPTIONS** | |
| Multifunctional accessory with quick-release coupling | – |
| Jump-start cable | ● |
| Oil cooler | ● |
| Drain line | ○ |
| 3-point rear linkage | – |
| Quick boom coupling | – |
| Stabiliser leg | ○ |

– NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

**Your Merlo dealer**

**MERLO S.P.A.**
Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111
info@merlo.com www.merlo.com

Release 8/10/2026 - 11:58

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.