

Medium Capacity Telehandlers

Turbofarmer 33.9



**PERFORMANCE AND FEATURES****TF33.9CS-140****TF33.9-140****Performance**

Unladen weight (kg)	7450	7300
Maximum load capacity (kg)	3300	3300
Lift height (m)	8,6	8,6
Maximum reach (m)	5,7	5,7
Lift height at max. load capacity (m)	6,2	6,2
Reach at max. load capacity (m)	1,6	1,6
Load capacity at max. lift height (m)	1750	1750
Load capacity at max. reach (kg)	650	650
Boom side-shift (mm)	-	-
Frame levelling (%)	-	-
Boom section	3	3

**Powertrain**

Engine	Deutz TCD 3.6	Deutz TCD 3.6
Range/Cylinders	3600/4	3600/4
Engine power (kW/HP)	100/136	100/136
Anti-pollution technology	Stage V - SCR + DPF + DOC	Stage V - SCR + DPF + DOC
Reversible Fan	●	●
Maximum speed (km/h)	40	40
Fuel tank capacity (l)	85	85
AdBlue tank capacity (l)	12	12
Hydrostatic transmission	YES - 2V	YES - 2V
EPD	PLUS	PLUS
Joystick autoaccelerante	STD	STD
Axles	Axial	Axial
Reducers	Epicyclic	Epicyclic
Brakes	Dry discs	Dry discs

**Hydraulic**

Hydraulic pump	LS+FS	LS+FS
Delivery / pressure (L / MIN - BAR)	125 - 210	125 - 210
Hydraulic oil tank capacity (l)	85	85
Auxiliary hydraulic service on boom	●	●
Rear service line	○	○


**Cab**

Cab finishing	ECO	ECO
ASCS	Light	Light
FOPS II Cab	●	●
ROPS Cab	●	●
Controls	Electronic joystick control	Electronic joystick control
Tilting cab	—	—
Reverse shuttle	Dual reverse	Dual reverse

**Configuration**

Hydropneumatic Suspension CS Merlo	●	—
Hydropneumatic Suspension BSS Merlo	○	○
Hydropneumatic Suspension EAS Merlo	—	—
Work lights on cab	●	●
Sun-shade in the cab	○	○
Tac-lock	●	●
Pre-arrangement for aerial work platform	○	○
Two floating forks	●	●
Pedal Inching-Control	●	●
Permanent four-wheel drive	●	●
All wheel steering	●	●
Three steering way	●	●
Standard tyres	—	—
OPT tyres	—	—
Hydraulically controlled stabilizers	—	—
Turret rotation	—	—
Tractor type approval	○	○
Pneumatic brakes (ton)	○	○
Hydraulic brakes (ton)	○	○
PTO	—	—
3-point rear linkage	—	—

— not available
 ● standard
 ○ optional



Dimensions



	TF33.9CS-140	TF33.9-140	
A - Length	4330	990	
C - Wheelbase	2740	3910	
F - Ground clearance	380	380	
H - Width	2250	2250	
M - Cabin width	1010	1010	
P - Height	2300	2240	
R - Turning radius at wheels	4095	4095	
S - Turning radius at forks	4740	4740	

Your Merlo dealer

MERLO S.P.A.

Via Nazionale, 9

12010 S. Defendente di Cervasca, (Cuneo) Italia

Tel. +39 0171 614111

Fax +39 0171 684101

info@merlo.com

www.merlo.com



