


# Medium Capacity Telehandlers

Regulatory area: EE  
TF33.9

**MERLO**



MODEL	TF33.9-115EE
A - Length (mm)	4330
C - Wheelbase (mm)	2740
F - Ground clearance (mm)	380
H - Width (mm)	2250
M - Cab width (mm)	1010
P - Height (mm)	2240
S - Fork steering range (mm)	4740



MODEL	TF33.9-115EE
<b>PERFORMANCE</b>	
Unladen weight (kg)	7200
Maximum load capacity (kg)	3300
Lift height (m)	8.6
Maximum reach (m)	5.7
Boom side-shift (mm)	—
Frame levelling (%)	—
Boom section	3
<b>POWERTRAIN</b>	
Engine	DEUTZ TCD 3.6
Range/Cylinders (l)	3.6/4
Engine power (kW/HP)	85/115
Anti-pollution technology	Tier 3
Reversible Fan	●
Maximum speed (km/h)	40
Fuel tank capacity (l)	85
AdBlue tank capacity (l)	—
Hydrostatic transmission EPD	●
Electronic joystick	●
Axles	Axial
Brakes	Dry discs
<b>HYDRAULIC</b>	
Delivery / pressure (bar-l/min)	125-210
Hydraulic oil tank capacity (l)	85
<b>CAB</b>	
ASCS	Light
FOPS/ROPS Cab	●
Tilting cab	—
<b>CONFIGURATION</b>	
Hydropneumatic Suspension CS Merlo	—
Frame suspension	—
Permanent four-wheel drive	●
Three steering way	●
Standard tyres	400/70-24"
Hydraulically controlled stabilizers	—
Turret rotation	—
PTO (rpm)	—
3-point rear linkage (kg)	—

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer



**MERLO S.P.A.**

Via Nazionale, 9  
12010 S. Defendente di Cervasca, (Cuneo) Italia  
Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 4/03/2026 - 7:33

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.