
High Capacity Telehandlers



Regulatory area: EU P72.10



MODEL	P72.10PLUS
A - Length (mm)	5480
C - Wheelbase (mm)	2920
F - Ground clearence (mm)	450
H - Width (mm)	2310
M - Cab width (mm)	1010
P - Height (mm)	2500
S - Fork steering range (mm)	4990



MODEL	P72.10PLUS
PERFORMANCE	
Unladen weight (kg)	11300
Maximum load capacity (kg)	7200
Lift height (m)	9.55
Maximum reach (m)	5.2
Boom side-shift (mm)	+/- 250
Frame levelling (%)	+/-8
Boom section	2
POWERTRAIN	
Engine	PERKINS 904
Range/Cylinders (I)	3.6/4
Engine power (kW/HP)	85.9/116.8
Anti-pollution technology	Stage V - SCR + DOC + DPF
Reversible Fan	•
Maximum speed (km/h)	40
Fuel tank capacity (I)	140
AdBlue tank capacity (I)	16
Hydrostatic transmission EPD	•
Electronic joystick	•
Axles	Drop portal
Brakes	Dry discs
HYDRAULIC	
Delivery / pressure (bar-l/min)	108-250
Hydraulic oil tank capacity (I)	100
CAB	
ASCS	Full
FOPS/ROPS Cab	•
Tilting cab	-
CONFIGURATION	
Hydropneumatic Suspension CS Merlo	-
Hydropneumatic Suspension EAS Merlo	-
Permanent four-wheel drive	•
Three steering way	•
Standard tyres	400/70-24"
Hydraulically controlled stabilizers	_
Turret rotation	-
PTO (rpm)	_
3-point rear linkage (kg)	_

NOT AVAILABLE
◆ STANDARD
◆ O OPTIONAL

Your Merio dealer



MERLO S.P.A.

Via Nazionale, 9 12010 S. Defendente di Cervasca, (Cuneo) Italia Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 3/11/2025 - 10:49

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.