
## High Capacity Telehandlers

MERLO

Regulatory area: NA P120.10HM



MODEL	P120.10HM
A - Lenght (in)	227
C - Wheelbase (in)	130
F - Ground clearence (in)	18
H - Width (in)	99
M - Cab width (in)	40
P - Height (in)	112
S - Fork steering range (in)	224



MODEL	P120.10HM
PERFORMANCE	
Unladen weight (lb)	35715
Maximum load capacity (lb)	24000
Lift height (ft)	32'
Maximum reach (ft)	17'
Boom side-shift (in)	+/- 7.3
Frame levelling (%)	+/- 8
Boom section	2
POWERTRAIN	
Engine	FPT NEF45
Range/Cylinders (I)	4.5/4
Engine power (kW/HP)	125/170
Anti-pollution technology	Stage V - SCR + DOC + DPF
Reversible Fan	_
Maximum speed (mph)	25
Fuel tank capacity (gal)	40
AdBlue tank capacity (gal)	11.4
Hydrostatic transmission EPD	CVTronic
Electronic joystick	STD
Axles	Axial
Brakes	Wet discs
HYDRAULIC	
Delivery / pressure (gal/min-psi)	41.7 - 3046
Hydraulic oil tank capacity (gal)	39.3
CAB	
ASCS	Full
FOPS/ROPS Cab	•
Tilting cab	_
CONFIGURATION	
Hydropneumatic Suspension CS Merlo	_
Hydropneumatic Suspension EAS Merlo	_
Permanent four-wheel drive	•
Three steering way	•
Standard tyres	17.5-25"
Hydraulically controlled stabilizers	_
Turret rotation	-
PTO (rpm)	_
3-point rear linkage (lb)	-

NOT AVAILABLE
◆ STANDARD
◆ O OPTIONAL

Your Merio dealer



## MERLO S.P.A.

Via Nazionale, 9 12010 S. Defendente di Cervasca, (Cuneo) Italia Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 21/11/2025 - 8:25

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.