

Medium Capacity Telehandlers


TF33.9-140EE4





PERFORMANCE AND FEATURES	TF33.9-140EE4	TF33.9CS-140EE4	
Performance			
Total unladen weight (lb)	15322	16424	
Maximum capacity (lb)	7300	7300	
Lifting height (ft)	28' 2"	28' 2"	
Maximum reach (ft)	18' 7"	18' 7"	
Maximum operating height (ft)	19' 9"	19' 9"	
Maximum operating reach (ft)	4' 9"	4' 9"	
Capacity at maximum height (lb)	3800	3800	
Capacity at maximum reach (lb)	1300	1300	
Lateral boom movement (inch)	-	-	
Tilting correction (%)	-	-	
Boom sections	3	3	
PowerTrain			
Turbo motor	DEUTZ TCD3.6	DEUTZ TCD3.6	
Displacement/cylinders	3600/4	3600/4	
Engine Power (kW/HP)	100/136	100/136	
Anti-pollution technology	TIER 4 - SCR + DOC	TIER 4 - SCR + DOC	
Reversible fan	●	●	
Maximum speed (mph)	25	25	
Fuel tank (gal)	22.5	22.5	
AdBlue tank (gal)	3.2	3.2	
Hydrostatic transmission	● - 2V	● - 2V	
EPD	Plus	Plus	
Auto-revving joystick	●	●	
Axles - Reducers	Axial, Epicyclic	Axial, Epicyclic	
Machine brakes	Dry disc	Dry disc	
Automatic parking brake	●	●	
Hydraulic			
Hydraulic pump	LS+FS	LS+FS	
Flow rate/pressure (gal/min - psi)	33 - 3046	33 - 3046	
Hydraulic tank	22.5	22.5	
Hydraulic outlet at the top of the boom	●	●	
Rear hydraulic outlets	○	○	
Cab			
Cab configuration	ECO	ECO	
ASCS Adaptive Stability Control System	Light	Light	
FOPS LIV II cab	●	●	
ROPS cab	●	●	
Cab commands	Electronic joystick	Electronic joystick	
Tilting Cab	-	-	
Reverse shuttle	Dual reverse	Dual reverse	
Configuration			
Cab suspension	-	●	
Boom suspension	○	○	
Suspension on axles	-	-	
Work headlights on cab	●	●	
Sun blind	○	○	
Tac-lock	●	●	
Provision for a platform	○	○	
Two floating forks	●	●	
Inching-Control	●	●	
Four-wheel drive	●	●	
Four-wheel steering	●	●	
Three steering modes	●	●	
Standard tyres	400/70-24"	400/70-24"	
Optional tyres	460/70 24"	460/70 24"	
Stabilisers	-	-	
Turret rotation	-	-	
Type approval as an agricultural tractor	-	-	
Approval with PNEUMATIC braking	○	○	
Approval with HYDRAULIC braking	○	○	
PTO	-	-	
3-point linkage	-	-	

- Not Available
● Standard
○ Optional




TF33.9-140EE4


Dimensions



	TF33.9 140EE4	TF33.9CS 140EE4	
A (inch)	170.5	170.5	
B (inch)	39.0	39.0	
C (inch)	107.9	107.9	
D (inch)	23.6	23.6	
E (inch)	153.9	153.9	
F (inch)	15.0	15.0	
H (inch)	88.6	88.6	
M (inch)	39.8	39.8	
P (inch)	88.2	90.6	
R (inch)	161.2	161.2	
S (inch)	186.6	186.6	
Z (inch)	33.5	33.5	



Your Merlo dealer



TF33.9-140EE4:

... - VIN: ... - SAV: ... - ...

TF33.9CS-140EE4:

MA00830 - VIN: D1005168 - SAV: D142191 - 15/11/2021

MERLO S.P.A.

Via Nazionale, 9

12010 S. Defendente di Cervasca, (Cuneo) Italia

Tel. +39 0171 614111

Fax +39 0171 684101

info@merlo.com

www.merlo.com

