

# Electric Cingo

Regulatory area: EU

## M600TD-e



| MODEL                  | M600TD-E  |
|------------------------|-----------|
| Height                 | 1200      |
| Rubber track dimension | 180x72x36 |
| Ground clearance       | 77        |
| Width (mm)             | 753       |
| Length (mm)            | 1560      |

| MODEL                                                 | M600TD-E    |
|-------------------------------------------------------|-------------|
| <b>OPERATOR WORKSTATION</b>                           |             |
| Shock-absorbing Operator Platform                     | ●           |
| Lever controls                                        | ●           |
| Engine status display                                 | ●           |
| Operator support handle                               | ●           |
| <b>ENGINE</b>                                         |             |
| Electric Starter                                      | ●           |
| Battery (Electric only)                               | 7,2         |
| Inverter (Electric only)                              | ●           |
| Fuel                                                  | Electric    |
| Displacement/Cylinders (l)                            | —           |
| Engine                                                | Electric    |
| Engine Power (hp/kW)                                  | —           |
| Transmission type                                     | Electric    |
| Track support rollers                                 | 4           |
| Gear motors                                           | ●           |
| Hydrostatic pump                                      | —           |
| Fuel tank capacity (l)                                | —           |
| Hydraulic oil tank capacity (l)                       | 9           |
| Anti-pollution technology                             | 0 emissions |
| Cooling system                                        | —           |
| <b>OPTIONS</b>                                        |             |
| Multifunctional accessory with quick-release coupling | —           |
| Jump-start cable                                      | —           |
| Oil cooler                                            | —           |
| Drain line                                            | —           |
| 3-point rear linkage                                  | —           |
| Quick boom coupling                                   | —           |
| Stabiliser leg                                        | —           |
| <b>PERFORMANCE</b>                                    |             |
| Dumper capacity (m3)                                  | 0,33        |
| Unladen weight (kg)                                   | 500         |
| Maximum cross gradient (%)                            | 20          |
| Maximum longitudinal gradient (%)                     | 35          |
| Maximum load capacity (kg)                            | 600         |
| Maximum speed (km/h)                                  | 3-5         |
| Implement pump                                        | 3,5         |
| Implement pump delivery (l/min)                       | 8           |

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

**Your Merlo dealer**



**MERLO S.p.A.**

Via Nazionale, 9  
12010 S. Defendente di Cervasca, (Cuneo) Italia  
Tel. +39 0171 614111

[info@merlo.com](mailto:info@merlo.com) [www.merlo.com](http://www.merlo.com)

Release 27/07/2026 - 9:5

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.