Electric Cingo

Regulatory area: EU

M600TD-e



MODEL	M600TD-E
Height (mm)	1200
Rubber track dimension (mm)	180x72x36
Ground clearance (mm)	77
Width (mm)	753
Length (mm)	1560

MODEL	M600TD-E
OPERATOR WORKSTATION	
Shock-absorbing Operator Platform	●
Lever controls	●
Engine status display	●
Operator support handle	●
ENGINE	
Electric Starter	●
Battery (Electric only)	7,2
Inverter (Electric only)	●
Fuel	Electric
Displacement/Cylinders (cc/n°)	–
Engine	Electric
Engine Power (hp/kW)	–
Transmission type	Electric
Track support rollers	4
Gear motors	●
Hydrostatic pump	–
Fuel tank capacity (l)	–
Hydraulic oil tank capacity (l)	9
Anti-pollution technology	0 emissions
Cooling system	–
OPTIONS	
Multifunctional accessory with quick-release coupling	–
Jump-start cable	–
Oil cooler	–
Drain line	–
3-point rear linkage	–
Quick boom coupling	–
Stabiliser leg	–
PERFORMANCE	
Dumper capacity (m3)	0,33
Unladen weight (kg)	500
Maximum cross gradient (%)	20
Maximum longitudinal gradient (%)	35
Maximum load capacity (kg)	600
Maximum speed (km/h)	3-5
Implement pump	3,5
Implement pump delivery (l/min)	8

– NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer

MERLO S.P.A.
Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111
info@merlo.com www.merlo.com

Release 8/10/2026 - 9:57

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.