Cingo Tool Carrier

Regulatory area: AU

M4.3EVO



MODEL	M4.3EVO
Height (mm)	1460
Rubber track dimension (mm)	180x72x45
Ground clearance (mm)	187
Width (mm)	680
Length (mm)	1950

MODEL	M4.3EVO
PERFORMANCE	
Dumper capacity (m3)	—
Unladen weight (kg)	700
Maximum cross gradient (%)	20
Maximum longitudinal gradient (%)	35
Maximum load capacity (kg)	400
Maximum speed (km/h)	6
Implement pump	6+4
Implement pump delivery (l/min)	18+12
OPERATOR WORKSTATION	
Shock-absorbing Operator Platform	●
Lever controls	●
Engine status display	●
Operator support handle	●
ENGINE	
Electric Starter	●
Battery (Electric only)	—
Inverter (Electric only)	—
Fuel	Diesel
Displacement/Cylinders (cc/n°)	1130/3
Engine	Kubota D1105
Engine Power (hp/kW)	25/18,4
Transmission type	Hydrostatic
Track support rollers	6
Gear motors	●
Hydrostatic pump	●
Fuel tank capacity (l)	25
Hydraulic oil tank capacity (l)	23
Anti-pollution technology	Stage V
Cooling system	Liquid
OPTIONS	
Multifunctional accessory with quick-release coupling	—
Jump-start cable	—
Oil cooler	●
Drain line	●
3-point rear linkage	—
Quick boom coupling	—
Stabiliser leg	—

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer

MERLO S.P.A.
Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111
info@merlo.com www.merlo.com

Release 8/10/2026 - 11:46

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.