

Dumper
Regulatory area: NA
DM



MODEL	DM9
Length (in)	194
Wheelbase	108
Ground clearance	20
Width (in)	92
Cab width	36
Wheel steering range	165

MODEL	DM9
PERFORMANCE	
Unladen weight (lb)	17857
Maximum load capacity (lb)	19842
3-point linkage capacity (lb)	—
Maximum cross gradient	15%
Maximum gradient unladen	50%
Concrete yield	—
Fifth wheel rotation	±90°
POWERTRAIN	
Engine	Deutz TCD3.6
Displacement / Cylinders (gal)	0.95/4
Engine power (kW/HP)	74.4/100
Anti-pollution technology	Stage V
Fuel tank capacity (gal)	53
AdBlue tank capacity (gal)	5
Transmission type	Hydrostatic
Axles	Drop portal
Brakes	4 dry disc
Automatic parking brake	●
Number of gears	2
Maximum speed (mph)	25
HYDRAULIC	
Hydraulic pump	LS
Delivery / Pressure (gal/min-psi)	18.76-3.046
CAB	
Seat with pneumatic suspension	—
ROPS cab	STANDARD
Cab controls	Electro-hydraulic joystick
CONFIGURATION	
Cab suspension	—
Sun-shade	○
Permanent four-wheel drive	●
All-wheel steering	●
Standard tyres	18-19.5"
Rear tow hooks	STANDARD
Automatic battery disconnect switch	●
Rear Camera	●
Steering modes	3

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer



MERLO S.P.A.

Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 1/09/2026 - 7:45

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.