
## Compact Telehandlers Regulatory area: EE

## **TF27.6**





MODEL	TF27.6EE4
A - Length (mm)	3910
C - Wheelbase (mm)	2450
F - Ground clearence (mm)	330
H - Width (mm)	1860
M - Cab width (mm)	1010
P - Height (mm)	2020
S - Fork steering range (mm)	4200



MODEL	TF27.6EE4
PERFORMANCE	
Unladen weight (kg)	4850
Maximum load capacity (kg)	2700
Lift height (m)	5.9
Maximum reach (m)	3.3
Boom side-shift (mm)	-
Frame levelling (%)	_
Boom section	2
POWERTRAIN	
Engine	KOHLER 2504 TCR
Range/Cylinders (I)	2.5/4
Engine power (kW/HP)	55.4/75.1
Anti-pollution technology	Tier 4 DOC
Reversible Fan	_
Maximum speed (km/h)	40
Fuel tank capacity (I)	70
AdBlue tank capacity (I)	_
Hydrostatic transmission EPD	TOP - 1V
Electronic joystick	_
Axles	Axial
Brakes	Dry discs
HYDRAULIC	
Delivery / pressure (bar-l/min)	95-210
Hydraulic oil tank capacity (I)	70
CAB	
ASCS	Light
FOPS/ROPS Cab	•
Tilting cab	_
CONFIGURATION	
Hydropneumatic Suspension CS Merlo	_
Hydropneumatic Suspension EAS Merlo	_
Permanent four-wheel drive	•
Three steering way	•
Standard tyres	12/75-18"
Hydraulically controlled stabilizers	<del>-</del>
Turret rotation	_
PTO (rpm)	_
3-point rear linkage (kg)	_

NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merio dealer



## MERLO S.P.A.

Via Nazionale, 9 12010 S. Defendente di Cervasca, (Cuneo) Italia Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 3/11/2025 - 16:2

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.