
## High Capacity Telehandlers



Regulatory area: **EE** TF50.8



MODEL	TF50.8T-170EE-HF
A - Length (mm)	4870
C - Wheelbase (mm)	3050
F - Ground clearence (mm)	440
H - Width (mm)	2400
M - Cab width (mm)	1010
P - Height (mm)	2530
S - Fork steering range (mm)	4800



MODEL	TF50.8T-170EE-HF
PERFORMANCE	
Unladen weight (kg)	9700
Maximum load capacity (kg)	5000
Lift height (m)	7.8
Maximum reach (m)	4.2
Boom side-shift (mm)	-
Frame levelling (%)	+/-8
Boom section	2
POWERTRAIN	
Engine	FPT NEF45
Range/Cylinders (I)	4.5/4
Engine power (kW/HP)	125/170
Anti-pollution technology	Tier 2
Reversible Fan	0
Maximum speed (km/h)	40
Fuel tank capacity (I)	140
AdBlue tank capacity (I)	_
Hydrostatic transmission EPD	•
Electronic joystick	•
Axles	Axial
Brakes	Dry discs
HYDRAULIC	
Delivery / pressure (bar-l/min)	160-250
Hydraulic oil tank capacity (I)	100
CAB	
ASCS	Full
FOPS/ROPS Cab	•
Tilting cab	-
CONFIGURATION	
Hydropneumatic Suspension CS Merlo	_
Hydropneumatic Suspension EAS Merlo	<del>-</del>
Permanent four-wheel drive	•
Three steering way	•
Standard tyres	500/70-24"
Hydraulically controlled stabilizers	<del>-</del>
Turret rotation	_
PTO (rpm)	_
3-point rear linkage (kg)	_

NOT AVAILABLE
◆ STANDARD
◆ O OPTIONAL

Your Merio dealer



## MERLO S.P.A.

Via Nazionale, 9 12010 S. Defendente di Cervasca, (Cuneo) Italia Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 4/11/2025 - 7:53

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.