
Telescopic Tractors Regulatory area: EU

MF44.7





MODEL	MF44.7CS-170-CVT
A - Length (mm)	5370
C - Wheelbase (mm)	2950
F - Ground clearence (mm)	440
H - Width (mm)	2400
M - Cab width (mm)	1010
P - Height (mm)	2590
S - Fork steering range (mm)	4860



MODEL	MF44.7CS-170-CVT
PERFORMANCE	
Unladen weight (kg)	9080
Maximum load capacity (kg)	4400
Lift height (m)	6.8
Maximum reach (m)	3.8
Boom side-shift (mm)	_
Frame levelling (%)	+/-8
Boom section	2
POWERTRAIN	
Engine	FPT NEF45
Range/Cylinders (I)	4.5/4
Engine power (kW/HP)	125/170
Anti-pollution technology	Stage V - SCR + DOC + DPF
Reversible Fan	0
Maximum speed (km/h)	40
Fuel tank capacity (I)	140
AdBlue tank capacity (I)	18
Hydrostatic transmission EPD	CVTronic
Electronic joystick	•
Axles	Axial
Brakes	Dry discs
HYDRAULIC	
Delivery / pressure (bar-l/min)	150-210
Hydraulic oil tank capacity (I)	100
CAB	
ASCS	Full
FOPS/ROPS Cab	•
Tilting cab	_
CONFIGURATION	
Hydropneumatic Suspension CS Merlo	•
Hydropneumatic Suspension EAS Merlo	_
Permanent four-wheel drive	•
Three steering way	•
Standard tyres	500/70-24"
Hydraulically controlled stabilizers	_
Turret rotation	-
PTO (rpm)	540/1000
3-point rear linkage (kg)	CAT III -7000 Kg

NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merio dealer



MERLO S.P.A.

Via Nazionale, 9 12010 S. Defendente di Cervasca, (Cuneo) Italia Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 3/11/2025 - 9:42

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.