Concrete Mixer
Regulatory area: EU
DBM



MODEL	DBM2500	DBM3500
Length (mm)	5250	5460
Wheelbase (mm)	2750	2750
Ground clearance (mm)	470	495
Width (mm)	2300	2335
Cab width (mm)	920	920
Maximum height (mm)	2975	3000
Wheel steering range (mm)	4165	4190

MODEL	DBM2500	DBM3500
PERFORMANCE		
Unladen weight (kg)	7050	7400
Maximum cross gradient	15%	15%
Maximum gradient unladen	45%	45%
Concrete yield (l)	2500	3500
Fifth wheel rotation	±90°	±90°
POWERTRAIN		
Engine	Deutz TCD3.6	Deutz TCD3.6
Displacement / Cylinders (l)	3.6/4	3.6/4
Engine power (kW/HP)	74.4/100	74.4/100
Anti-pollution technology	Stage V	Stage V
Fuel tank capacity (l)	200	200
AdBlue tank capacity (l)	18	18
Transmission type	Hydrostatic	Hydrostatic
Axles	Drop portal	Drop portal
Brakes	4 dry disc	4 dry disc
Automatic parking brake	●	●
Number of gears	2	2
Maximum speed (km/h)	40	40
HYDRAULIC		
Hydraulic pump	LS	LS
Delivery / Pressure (l/min - bar)	103-210	103-210
CAB		
Seat with pneumatic suspension	—	—
ROPS cab	STANDARD	STANDARD
Cab controls	Levers	Levers
CONFIGURATION		
Cab suspension	—	—
Sun-shade	—	—
Permanent four-wheel drive	●	●
All-wheel steering	●	●
Standard tyres	405/70-20"	18-19.5"
Rear tow hooks	●	●
Automatic battery disconnect switch	●	●
Rear Camera	●	●
Steering modes	3	3

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer

MERLO S.P.A.
Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111
info@merlo.com www.merlo.com

Release 7/10/2026 - 7:23

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.