

Tool Handler Tractors

Regulatory area: NA

TREEMME X



MODEL	MM250X	MM350X
Length (in)	210	224
Wheelbase	104	110
Ground clearance	20	18
Width (in)	97	97
Cab width	47	47
Wheel steering range	163	171

MODEL	MM250X	MM350X
PERFORMANCE		
Unladen weight (lb)	17637	20282
Maximum load capacity (lb)	—	—
3-point linkage capacity (lb)	9921	9921
Maximum cross gradient	30%	30%
Maximum gradient unladen	60%	60%
Concrete yield	—	—
Fifth wheel rotation	—	—
POWERTRAIN		
Engine	Deutz 6.1	Deutz 7.8
Displacement / Cylinders (gal)	1.61/6	2.06/6
Engine power (kW/HP)	180	250
Anti-pollution technology	Stage V	Stage V
Fuel tank capacity (gal)	70	92
AdBlue tank capacity (gal)	8.5	13.21
Transmission type	Hydrostatic	Hydrostatic
Axles	Axial	Axial
Brakes	Wet disc	Wet disc
Automatic parking brake	●	●
Number of gears	2	2
Maximum speed (mph)	25	22
HYDRAULIC		
Hydraulic pump	LS	LS
Delivery / Pressure (gal/min-psi)	31.70-3.336	31.70-3.336
CAB		
Seat with pneumatic suspension	●	●
ROPS cab	●	●
Cab controls	Joystick	Joystick
CONFIGURATION		
Cab suspension	—	—
Sun-shade	○	○
Permanent four-wheel drive	●	●
All-wheel steering	●	●
Standard tyres	600/55 - 26.5	600/55 - 26.5
Rear tow hooks	●	●
Automatic battery disconnect switch	●	●
Rear Camera	○	○
Steering modes	○	○

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer



MERLO S.P.A.

Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 2/09/2026 - 6:17

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.