
## Stabilized Telehandlers



Regulatory area: **EE** P40.13



| MODEL                        | P40.13EE |
|------------------------------|----------|
| A - Length (mm)              | 5410     |
| C - Wheelbase (mm)           | 2810     |
| F - Ground clearence (mm)    | 375      |
| H - Width (mm)               | 2240     |
| M - Cab width (mm)           | 1010     |
| P - Height (mm)              | 2425     |
| S - Fork steering range (mm) | 4940     |



| MODEL                                | P40.13EE     |
|--------------------------------------|--------------|
| PERFORMANCE                          |              |
| Unladen weight (kg)                  | 9150         |
| Maximum load capacity (kg)           | 4000         |
| Lift height (m)                      | 12.5         |
| Maximum reach (m)                    | 8.7          |
| Boom side-shift (mm)                 | +/- 340      |
| Frame levelling (%)                  | +/- 8        |
| Boom section                         | 3            |
| POWERTRAIN                           |              |
| Engine                               | PERKINS 904  |
| Range/Cylinders (I)                  | 3.6/4        |
| Engine power (kW/HP)                 | 85.9/116.8   |
| Anti-pollution technology            | Tier 3       |
| Reversible Fan                       | •            |
| Maximum speed (km/h)                 | 40           |
| Fuel tank capacity (I)               | 140          |
| AdBlue tank capacity (I)             | _            |
| Hydrostatic transmission EPD         | •            |
| Electronic joystick                  | •            |
| Axles                                | Drop portal  |
| Brakes                               | Dry discs    |
| HYDRAULIC                            |              |
| Delivery / pressure (bar-l/min)      | 108-250      |
| Hydraulic oil tank capacity (I)      | 100          |
| CAB                                  |              |
| ASCS                                 | Light        |
| FOPS/ROPS Cab                        | •            |
| Tilting cab                          | _            |
| CONFIGURATION                        |              |
| Hydropneumatic Suspension CS Merlo   | _            |
| Hydropneumatic Suspension EAS Merlo  | _            |
| Permanent four-wheel drive           | •            |
| Three steering way                   | •            |
| Standard tyres                       | 400/70-20"   |
| Hydraulically controlled stabilizers | Narrow       |
| Turret rotation                      | <del>-</del> |
| PTO (rpm)                            | _            |
| 3-point rear linkage (kg)            | <del>-</del> |

NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

## Your Merio dealer



## MERLO S.P.A.

Via Nazionale, 9 12010 S. Defendente di Cervasca, (Cuneo) Italia Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 4/11/2025 - 8:5

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.