

Cingo Transporter
Regulatory area: EE
M8.3TD-EVO



MODEL	M8.3TDEVO
Height	1175
Rubber track dimension	180x72x36
Ground clearance	100
Width (mm)	800
Length (mm)	1800

MODEL	M8.3TDEVO
OPERATOR WORKSTATION	
Shock-absorbing Operator Platform	●
Lever controls	●
Engine status display	●
Operator support handle	●
ENGINE	
Electric Starter	●
Battery (Electric only)	—
Inverter (Electric only)	—
Fuel	Diesel
Displacement/Cylinders (l)	600
Engine	Kubota Z602
Engine Power (hp/kW)	17/12,5
Transmission type	Hydrostatic
Track support rollers	4
Gear motors	●
Hydrostatic pump	●
Fuel tank capacity (l)	14
Hydraulic oil tank capacity (l)	19
Anti-pollution technology	Stage V
Cooling system	Liquid
OPTIONS	
Multifunctional accessory with quick-release coupling	—
Jump-start cable	●
Oil cooler	●
Drain line	○
3-point rear linkage	—
Quick boom coupling	—
Stabiliser leg	○
PERFORMANCE	
Dumper capacity (m3)	0,33
Unladen weight (kg)	510
Maximum cross gradient (%)	20
Maximum longitudinal gradient (%)	35
Maximum load capacity (kg)	800
Maximum speed (km/h)	4
Implement pump	8+2,5
Implement pump delivery (l/min)	27+8

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer



MERLO S.p.A.

Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 27/07/2026 - 9:40

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.