

Cingo Transporter
Regulatory area: AU
M500



MODEL	M500
Height	1125
Rubber track dimension	160x72x33
Ground clearance	115
Width (mm)	690
Length (mm)	1471

MODEL	M500
OPERATOR WORKSTATION	
Shock-absorbing Operator Platform	—
Lever controls	●
Engine status display	—
Operator support handle	●
ENGINE	
Electric Starter	—
Battery (Electric only)	—
Inverter (Electric only)	—
Fuel	Gas
Displacement/Cylinders (l)	200
Engine	Honda GX200
Engine Power (hp/kW)	5,6/4,1
Transmission type	Hydraulics
Track support rollers	3
Gear motors	—
Hydrostatic pump	—
Fuel tank capacity (l)	3,1
Hydraulic oil tank capacity (l)	21
Anti-pollution technology	Stage V
Cooling system	Air
OPTIONS	
Multifunctional accessory with quick-release coupling	—
Jump-start cable	—
Oil cooler	—
Drain line	—
3-point rear linkage	—
Quick boom coupling	—
Stabiliser leg	—
PERFORMANCE	
Dumper capacity (m3)	0,23
Unladen weight (kg)	230
Maximum cross gradient (%)	20
Maximum longitudinal gradient (%)	35
Maximum load capacity (kg)	500
Maximum speed (km/h)	3,5
Implement pump	3,2
Implement pump delivery (l/min)	10

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer



MERLO S.p.A.

Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 27/07/2026 - 9:23

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.