

Stabilized Telehandlers

Regulatory area: NA
P40.17



MODEL	P40.17EE4	P40.17PLUS
A - Lenght (in)	235	235
C - Wheelbase (in)	116	116
F - Ground clearance (in)	18	18
H - Width (in)	95	95
M - Cab width (in)	40	40
P - Height (in)	98	98
S - Fork steering range (in)	203	203

MODEL	P40.17EE4	P40.17PLUS
PERFORMANCE		
Unladen weight (lb)	25728	25728
Maximum load capacity (lb)	7900	7900
Lift height (ft)	54'	54'
Maximum reach (ft)	41'	41'
Boom side-shift (in)	+/- 17.1	+/- 17.1
Frame levelling (%)	+/- 8	+/- 8
Boom section	3	3
POWERTRAIN		
Engine	REHLKO 2504	PERKINS 904
Range/Cylinders (l)	2.5/4	3.6/4
Engine power (kW/HP)	55.4/75.1	85.9/115
Anti-pollution technology	Tier 4 - DOC	Stage V - SCR + DOC + DPF
Reversible Fan	●	●
Maximum speed (mph)	20.5	25
Fuel tank capacity (gal)	37	37
AdBlue tank capacity (gal)	—	4.8
Hydrostatic transmission EPD	●	●
Electronic joystick	STD	STD
Axles	Drop portal	Drop portal
Brakes	Dry discs	Dry discs
HYDRAULIC		
Delivery / pressure (gal/min-psi)	27.5 - 3626	27.5 - 3626
Hydraulic oil tank capacity (gal)	26.4	26.4
CAB		
ASCS	Light	Full
FOPS/ROPS Cab	●	●
Tilting cab	—	—
CONFIGURATION		
Hydropneumatic Suspension CS Merlo	—	—
Hydropneumatic Suspension EAS Merlo	—	—
Permanent four-wheel drive	●	●
Three steering way	●	●
Standard tyres	400/70-24"	400/70-24"
Hydraulically controlled stabilizers	Narrow	Narrow
Turret rotation	—	—
PTO (rpm)	—	—
3-point rear linkage (lb)	—	—

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer



MERLO S.P.A.

Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 22/01/2026 - 14:29

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.