Cingo Multifunction

Regulatory area: AU

M12.3EVO



MODEL	M12.3EVO
Height (mm)	1144
Rubber track dimension (mm)	230x72x40
Ground clearance (mm)	110
Width (mm)	1000
Length (mm)	1800

MODEL	M12.3EVO
PERFORMANCE	
Dumper capacity (m3)	0,55
Unladen weight (kg)	720
Maximum cross gradient (%)	20
Maximum longitudinal gradient (%)	35
Maximum load capacity (kg)	1200
Maximum speed (km/h)	5
Implement pump	8+2,5
Implement pump delivery (l/min)	27+8
OPERATOR WORKSTATION	
Shock-absorbing Operator Platform	●
Lever controls	●
Engine status display	●
Operator support handle	●
ENGINE	
Electric Starter	●
Battery (Electric only)	–
Inverter (Electric only)	–
Fuel	Diesel
Displacement/Cylinders (cc/n°)	720/3
Engine	Kubota D722
Engine Power (hp/kW)	20,3/14,9
Transmission type	Hydrostatic
Track support rollers	4
Gear motors	●
Hydrostatic pump	●
Fuel tank capacity (l)	14
Hydraulic oil tank capacity (l)	26
Anti-pollution technology	Stage V
Cooling system	Liquid
OPTIONS	
Multifunctional accessory with quick-release coupling	●
Jump-start cable	●
Oil cooler	●
Drain line	●
3-point rear linkage	○
Quick boom coupling	●
Stabiliser leg	○

– NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer

MERLO S.P.A.
Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111
info@merlo.com www.merlo.com

Release 8/10/2026 - 11:44

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.