Cingo Transporter
Regulatory area: NA
M700TD



MODEL	M700TD
Height (in)	48,4
Rubber track dimension (in)	71x28x14
Ground clearance (in)	3,9
Width (in)	29,5
Length (in)	64,6

MODEL	M700TD
PERFORMANCE	
Dumper capacity (ft³)	11,65
Unladen weight (lb)	1058
Maximum cross gradient (%)	20
Maximum longitudinal gradient (%)	35
Maximum load capacity (lb)	1543
Maximum speed (mph)	2,5
Implement pump	6
Implement pump delivery (gal/min)	20
OPERATOR WORKSTATION	
Shock-absorbing Operator Platform	●
Lever controls	●
Engine status display	—
Operator support handle	●
ENGINE	
Electric Starter	●
Battery (Electric only)	—
Inverter (Electric only)	—
Fuel	Gas
Displacement/Cylinders (gal)	23.8/1
Engine	Honda GX390
Engine Power (hp/kW)	11,8/8,7
Transmission type	Hydraulics
Track support rollers	4
Gear motors	●
Hydrostatic pump	—
Fuel tank capacity (gal)	1,6
Hydraulic oil tank capacity (gal)	3,9
Anti-pollution technology	Stage V
Cooling system	Air
OPTIONS	
Multifunctional accessory with quick-release coupling	—
Jump-start cable	—
Oil cooler	●
Drain line	○
3-point rear linkage	—
Quick boom coupling	—
Stabiliser leg	○

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer

MERLO S.P.A.
Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111
info@merlo.com www.merlo.com

Release 8/10/2026 - 11:48

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.