

Cingo Transporter
Regulatory area: NA
M8.3TD-EVO



MODEL	M8.3TDEV02
Height	46,3
Rubber track dimension	71x28x14
Ground clearance	3,9
Width (in)	31,5
Length (in)	70,9

MODEL	M8.3TDEV02
OPERATOR WORKSTATION	
Shock-absorbing Operator Platform	●
Lever controls	●
Engine status display	●
Operator support handle	●
ENGINE	
Electric Starter	●
Battery (Electric only)	—
Inverter (Electric only)	—
Fuel	Diesel
Displacement/Cylinders (gal)	159
Engine	Kubota Z602
Engine Power (hp/kW)	17/12,5
Transmission type	Hydrostatic
Track support rollers	4
Gear motors	●
Hydrostatic pump	●
Fuel tank capacity (gal)	3,7
Hydraulic oil tank capacity (gal)	5
Anti-pollution technology	Stage V
Cooling system	Liquid
OPTIONS	
Multifunctional accessory with quick-release coupling	—
Jump-start cable	●
Oil cooler	●
Drain line	○
3-point rear linkage	—
Quick boom coupling	—
Stabiliser leg	○
PERFORMANCE	
Dumper capacity (ft³)	11,65
Unladen weight (lb)	1124
Maximum cross gradient (%)	20
Maximum longitudinal gradient (%)	35
Maximum load capacity (lb)	1764
Maximum speed (mph)	2,5
Implement pump	8+2,5
Implement pump delivery (gal/min)	27+8

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer



MERLO S.P.A.

Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 27/07/2026 - 12:26

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.