

Cingo Multifunction

Regulatory area: NA

M12.3EVO



MODEL	M12.3EV02
Height	45
Rubber track dimension	91x28x16
Ground clearance	4,3
Width (in)	39,4
Length (in)	70,9

MODEL	M12.3EV02
OPERATOR WORKSTATION	
Shock-absorbing Operator Platform	●
Lever controls	●
Engine status display	●
Operator support handle	●
ENGINE	
Electric Starter	●
Battery (Electric only)	—
Inverter (Electric only)	—
Fuel	Diesel
Displacement/Cylinders (gal)	190
Engine	Kubota D722
Engine Power (hp/kW)	20,3/14,9
Transmission type	Hydrostatic
Track support rollers	4
Gear motors	●
Hydrostatic pump	●
Fuel tank capacity (gal)	3,7
Hydraulic oil tank capacity (gal)	6,8
Anti-pollution technology	Stage V
Cooling system	Liquid
OPTIONS	
Multifunctional accessory with quick-release coupling	●
Jump-start cable	●
Oil cooler	●
Drain line	●
3-point rear linkage	○
Quick boom coupling	●
Stabiliser leg	○
PERFORMANCE	
Dumper capacity (ft³)	19,42
Unladen weight (lb)	1587
Maximum cross gradient (%)	20
Maximum longitudinal gradient (%)	35
Maximum load capacity (lb)	2646
Maximum speed (mph)	3,1
Implement pump	8+2,5
Implement pump delivery (gal/min)	27+8

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer



MERLO S.p.A.

Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 27/07/2026 - 12:25

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.