Multipurpose Tractors

Regulatory area: EU

TREEMME 170R



MODEL	TREEMME 170R
Length (mm)	6000
Wheelbase (mm)	2650
Ground clearance (mm)	410
Width (mm)	2420
Cab width (mm)	1240
Maximum height (mm)	3100
Wheel steering range (mm)	4340

MODEL	TREEMME 170R
PERFORMANCE	
Unladen weight (kg)	9700
3-point linkage capacity (kg)	2500
POWERTRAIN	
Engine	Deutz TCD 4.0 L 4
Displacement / Cylinders (l)	3.94/4
Engine power (kW/HP)	129/175
Anti-pollution technology	Stage V
Fuel tank capacity (l)	200
AdBlue tank capacity (l)	20
Transmission type	Hydrostatic / Merlo CVTronic
Axles	Oscillating axles
Brakes	Wet discs
Automatic parking brake	●
Number of gears	2
Maximum speed (km/h)	40
HYDRAULIC	
Hydraulic pump	LS
Delivery / Pressure (l/min - bar)	115-230
CAB	
Seat with pneumatic suspension	●
OPS cab	○
Tilting cab for maintenance	●
Air-conditioning	●
CONFIGURATION	
Cab suspension	●
Permanent four-wheel drive	●
All-wheel steering	●
Standard tyres	460/70 R24
Rear tow hooks	●
Mechanical PTO	○
Automatic battery disconnect switch	●
Rear Camera	○
Steering modes	3 + 10PT
Brush cutter arm 8.5 M	○
Brush cutter arm 10 M	○

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer

MERLO S.P.A.
Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111
info@merlo.com www.merlo.com

Release 23/10/2026 - 7:2

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.