

Tool Handler Tractors

Regulatory area: EU

TREEMME X



MODEL	MM250X	MM350X
Length (mm)	5330	5690
Wheelbase	2650	2800
Ground clearance	500	465
Width (mm)	2470	2470
Cab width	1200	1200
Maximum height (bucket - air conditioner - beacon, etc.)	—	—
Wheel steering range	4130	4350

MODEL	MM250X	MM350X
PERFORMANCE		
Unladen weight (kg)	8000	9200
Maximum load capacity (kg)	—	—
3-point linkage capacity (kg)	4500	4500
Maximum cross gradient	30%	30%
Maximum gradient unladen	60%	60%
Concrete yield	—	—
Fifth wheel rotation	—	—
POWERTRAIN		
Engine	Deutz 6.1	Deutz 7.8
Displacement / Cylinders (l)	6.1/6	7.8/6
Engine power (kW/HP)	180	250
Anti-pollution technology	Stage V	Stage V
Fuel tank capacity (l)	265	350
AdBlue tank capacity (l)	32	50
Transmission type	Hydrostatic	Hydrostatic
Axles	Axial	Axial
Brakes	Wet disc	Wet disc
Automatic parking brake	●	●
Number of gears	2	2
Maximum speed (km/h)	40	36
HYDRAULIC		
Hydraulic pump	LS	LS
Delivery / Pressure (l/min - bar)	120-230	120-230
CAB		
Seat with pneumatic suspension	●	●
ROPS cab	●	●
Cab controls	Joystick	Joystick
CONFIGURATION		
Cab suspension	—	—
Sun-shade	○	○
Permanent four-wheel drive	●	●
All-wheel steering	●	●
Standard tyres	600/55 - 26.5	600/55 - 26.5
Rear tow hooks	●	●
Automatic battery disconnect switch	●	●
Rear Camera	○	○
Steering modes	○	○

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer



MERLO S.P.A.

Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 27/07/2026 - 15:20

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.