

# Medium Capacity Telehandlers

Turbofarmer 35.7





— not  
available  
● standard  
○ optional

## PERFORMANCE AND FEATURES

### Performance

Unladen weight (kg)

Maximum load capacity (kg)

Lift height (m)

Maximum reach (m)

Lift height at max. load capacity (m)

Reach at max. load capacity (m)

Load capacity at max. lift height (m)

Load capacity at max. reach (kg)

Boom side-shift (mm)

Frame levelling (%)

Boom section

### Powertrain

Engine

Range/Cylinders

Engine power (kW/HP)

Anti-pollution technology

Reversible Fan

Maximum speed (km/h)

Fuel tank capacity (l)

AdBlue tank capacity (l)

Hydrostatic transmission

EPD

Joystick autoaccelerante

Axles

Reducers

Brakes

Automatic parking brake

### Hydraulic

Hydraulic pump

Delivery / pressure (L / MIN – BAR)

Hydraulic oil tank capacity (l)

Auxiliary hydraulic service on boom

Rear service line

### Cab

Cab finishing

ASCS

FOPS II Cab

ROPS Cab

Controls

Tilting cab

Reverse shuttle

### Configuration

Hydropneumatic Suspension CS Merlo

Hydropneumatic Suspension BSS Merlo

Hydropneumatic Suspension EAS Merlo

Work lights on cab

Sun-shade in the cab

Tac-lock

Pre-arrangement for aerial work platform

Two floating forks

Pedal Inching-Control

Permanent four-wheel drive

All wheel steering

Three steering way

Standard tyres

OPT tyres

Hydraulically controlled stabilizers

Turret rotation

Tractor type approval

Pneumatic brakes (ton)

Hydraulic brakes (ton)

PTO

## TF35.7CS-140

6950  
3500  
6.6  
3.5  
6.5  
1.3  
3500  
1350  
-  
-  
2

3600/4  
100/136  
Stage V - SCR + DPF +  
DOC  
YES  
40  
85  
12  
YES - 2V  
PLUS  
STD  
Axial  
Epicyclic  
Dry discs  
YES

LS+FS  
125-210  
85  
●  
○  
ECO  
Light  
●  
●  
Electronic joystick control  
—  
Dual reverse

●  
○  
—  
●  
○  
●  
OPT  
YES  
YES  
YES  
●  
●  
400/70 - 24

—  
—  
○  
○  
○  
—  
—  
○  
○  
○

## TF35.7-140

6800  
3500  
6.6  
3.5  
6.5  
1.3  
3500  
1350  
-  
-  
2

3600/4  
100/136  
Stage V - SCR + DPF +  
DOC  
YES  
40  
85  
12  
YES - 2V  
PLUS  
STD  
Axial  
Epicyclic  
Dry discs  
YES

LS+FS  
125-210  
85  
●  
○  
ECO  
Light  
●  
●  
Electronic joystick control  
—  
Dual reverse

—  
○  
—  
●  
○  
●  
OPT  
YES  
YES  
YES  
●  
●  
400/70 - 24


—  
—  
○  
○  
○  
—  
—  
○  
○  
○

Dimensions



	TF35.7CS-140	TF35.7-140	
A - Lenght	4310	4310	
C - Wheelbase	2740	2740	
F - Ground clearence	380	380	
H - Width	2250	2250	
M - Cabin width	1010	1010	
P - Height	2300	2240	
R - Turning radius at wheels	4095	4095	
S - Turning radius at forks	4740	4740	

**Your Merlo dealer**



**MERLO S.P.A.**

Via Nazionale, 9

12010 S. Defendente di Cervasca, (Cuneo) Italia

Tel. +39 0171 614111

Fax +39 0171 684101

[info@merlo.com](mailto:info@merlo.com)

[www.merlo.com](http://www.merlo.com)



