

Concrete Mixer

Regulatory area: AU
DBM



MODEL	DBM2500	DBM3500
Length (mm)	5250	5460
Wheelbase	2750	2750
Ground clearance	470	495
Width (mm)	2300	2335
Cab width	920	920
Maximum height (bucket - air conditioner - beacon, etc.)	2975	3000
Wheel steering range	4165	4190

MODEL	DBM2500	DBM3500
PERFORMANCE		
Unladen weight (kg)	7050	7400
Maximum load capacity (kg)	2500	3500
3-point linkage capacity (kg)	—	—
Maximum cross gradient	15%	15%
Maximum gradient unladen	45%	45%
Concrete yield	2500	3500
Fifth wheel rotation	180°	180°
POWERTRAIN		
Engine	Deutz TCD3.6	Deutz TCD3.6
Displacement / Cylinders (l)	3.6/4	3.6/4
Engine power (kW/HP)	74.4/100	74.4/100
Anti-pollution technology	Stage V	Stage V
Fuel tank capacity (l)	200	200
AdBlue tank capacity (l)	18	18
Transmission type	Hydrostatic	Hydrostatic
Axles	Drop portal	Drop portal
Brakes	4 dry disc	4 dry disc
Automatic parking brake	●	●
Number of gears	2	2
Maximum speed (km/h)	40	40
HYDRAULIC		
Hydraulic pump	LS	LS
Delivery / Pressure (l/min - bar)	103-210	103-210
CAB		
Seat with pneumatic suspension	—	—
ROPS cab	STANDARD	STANDARD
Cab controls	Electro-hydraulic joystick	Electro-hydraulic joystick
CONFIGURATION		
Cab suspension	—	—
Sun-shade	—	—
Permanent four-wheel drive	●	●
All-wheel steering	●	●
Standard tyres	405/70-20"	18-19.5"
Rear tow hooks	STANDARD	STANDARD
Automatic battery disconnect switch	●	●
Rear Camera	STANDARD	STANDARD
Steering modes	3	3

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer



MERLO S.P.A.

Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 8/09/2026 - 11:51

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.