# Dumper

## Regulatory area: AU

## DM




| MODEL | DM9 |
|---|---|
| Length (mm) | 4920 |
| Wheelbase (mm) | 2750 |
| Ground clearance (mm) | 500 |
| Width (mm) | 2335 |
| Cab width (mm) | 920 |
| Maximum height (mm) | 3005 |
| Wheel steering range (mm) | 4190 |

| MODEL | DM9 |
|---|---|
| **PERFORMANCE** | |
| Unladen weight (kg) | 8100 |
| Maximum load capacity (kg) | 9000 |
| Maximum cross gradient | 15% |
| Maximum gradient unladen | 50% |
| Concrete yield (l) | — |
| Fifth wheel rotation | ±90° |
| **POWERTRAIN** | |
| Engine | Deutz TCD3.6 |
| Displacement / Cylinders (l) | 3.6/4 |
| Engine power (kW/HP) | 74.4/100 |
| Anti-pollution technology | Stage V |
| Fuel tank capacity (l) | 200 |
| AdBlue tank capacity (l) | 18 |
| Transmission type | Hydrostatic |
| Axles | Drop portal |
| Brakes | 4 dry disc |
| Automatic parking brake | ● |
| Number of gears | 2 |
| Maximum speed (km/h) | 40 |
| **HYDRAULIC** | |
| Hydraulic pump | LS |
| Delivery / Pressure (l/min - bar) | 71-210 |
| **CAB** | |
| Seat with pneumatic suspension | — |
| ROPS cab | STANDARD |
| Cab controls | Electro-hydraulic joystick |
| **CONFIGURATION** | |
| Cab suspension | — |
| Sun-shade | ○ |
| Permanent four-wheel drive | ● |
| All-wheel steering | ● |
| Standard tyres | 18-19.5" |
| Rear tow hooks | ● |
| Automatic battery disconnect switch | ● |
| Rear Camera | ● |
| Steering modes | 3 |

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

**Your Merlo dealer**

**MERLO S.P.A.**
Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111
info@merlo.com www.merlo.com

Release 7/10/2026 - 7:6

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.