

Dumper

Regulatory area: AU
DM



MODEL	DM9
Length (mm)	4920
Wheelbase	2750
Ground clearance	500
Width (mm)	2335
Cab width	920
Maximum height (bucket - air conditioner - beacon, etc.)	3005
Wheel steering range	4190

MODEL	DM9
PERFORMANCE	
Unladen weight (kg)	8100
Maximum load capacity (kg)	9000
3-point linkage capacity (kg)	—
Maximum cross gradient	15%
Maximum gradient unladen	50%
Concrete yield	—
Fifth wheel rotation	±90°
POWERTRAIN	
Engine	Deutz TCD3.6
Displacement / Cylinders (l)	3.6/4
Engine power (kW/HP)	74.4/100
Anti-pollution technology	Stage V
Fuel tank capacity (l)	200
AdBlue tank capacity (l)	18
Transmission type	Hydrostatic
Axles	Drop portal
Brakes	4 dry disc
Automatic parking brake	●
Number of gears	2
Maximum speed (km/h)	40
HYDRAULIC	
Hydraulic pump	LS
Delivery / Pressure (l/min - bar)	71-210
CAB	
Seat with pneumatic suspension	—
ROPS cab	STANDARD
Cab controls	Electro-hydraulic joystick
CONFIGURATION	
Cab suspension	—
Sun-shade	○
Permanent four-wheel drive	●
All-wheel steering	●
Standard tyres	18-19.5"
Rear tow hooks	STANDARD
Automatic battery disconnect switch	●
Rear Camera	●
Steering modes	3

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer



MERLO S.p.A.

Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 8/09/2026 - 11:52

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.