
## Stabilized Telehandlers



Regulatory area: EU P35.11



MODEL	P35.11
A - Length (mm)	5150
C - Wheelbase (mm)	2810
F - Ground clearence (mm)	460
H - Width (mm)	2310
M - Cab width (mm)	1010
P - Height (mm)	2530
S - Fork steering range (mm)	5200



MODEL	P35.11
PERFORMANCE	
Unladen weight (kg)	9000
Maximum load capacity (kg)	3500
Lift height (m)	11
Maximum reach (m)	7.8
Boom side-shift (mm)	+/- 310
Frame levelling (%)	+/-8
Boom section	3
POWERTRAIN	
Engine	KOHLER 2504
Range/Cylinders (I)	2.5/4
Engine power (kW/HP)	55.4/75.1
Anti-pollution technology	Stage V - DOC + DPF
Reversible Fan	•
Maximum speed (km/h)	33
Fuel tank capacity (I)	140
AdBlue tank capacity (I)	_
Hydrostatic transmission EPD	•
Electronic joystick	•
Axles	Drop portal
Brakes	Dry discs
HYDRAULIC	
Delivery / pressure (bar-l/min)	117-250
Hydraulic oil tank capacity (I)	100
CAB	
ASCS	Light
FOPS/ROPS Cab	•
Tilting cab	-
CONFIGURATION	
Hydropneumatic Suspension CS Merlo	-
Hydropneumatic Suspension EAS Merlo	-
Permanent four-wheel drive	•
Three steering way	•
Standard tyres	405/70-24"
Hydraulically controlled stabilizers	_
Turret rotation	_
PTO (rpm)	_
3-point rear linkage (kg)	_

NOT AVAILABLE
◆ STANDARD
◆ O OPTIONAL

Your Merio dealer



## MERLO S.P.A.

Via Nazionale, 9 12010 S. Defendente di Cervasca, (Cuneo) Italia Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 3/11/2025 - 13:58

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.