
Rotating Telehandlers Regulatory area: EE

ROTO40.16





| MODEL | ROTO40.16EE |
|------------------------------|-------------|
| A - Length (mm) | 6280 |
| C - Wheelbase (mm) | 2860 |
| F - Ground clearence (mm) | 290 |
| H - Width (mm) | 2240 |
| M - Cab width (mm) | 1010 |
| P - Height (mm) | 2980 |
| S - Fork steering range (mm) | 5930 |



| MODEL | ROTO40.16EE |
|--------------------------------------|-------------|
| PERFORMANCE | |
| Unladen weight (kg) | 12900 |
| Maximum load capacity (kg) | 4000 |
| Lift height (m) | 15.8 |
| Maximum reach (m) | 13.2 |
| Boom side-shift (mm) | - |
| Frame levelling (%) | _ |
| Boom section | 3 |
| POWERTRAIN | |
| Engine | FPT F34 |
| Range/Cylinders (I) | 3.4/4 |
| Engine power (kW/HP) | 55.4/75 |
| Anti-pollution technology | Tier 2 |
| Reversible Fan | - |
| Maximum speed (km/h) | 25 |
| Fuel tank capacity (I) | 140 |
| AdBlue tank capacity (I) | - |
| Hydrostatic transmission EPD | • |
| Electronic joystick | • |
| Axles | Drop portal |
| Brakes | Dry discs |
| HYDRAULIC | |
| Delivery / pressure (bar-l/min) | 103.5-250 |
| Hydraulic oil tank capacity (I) | 162 |
| CAB | |
| ASCS | Full |
| FOPS/ROPS Cab | • |
| Tilting cab | - |
| CONFIGURATION | |
| Hydropneumatic Suspension CS Merlo | - |
| Hydropneumatic Suspension EAS Merlo | - |
| Permanent four-wheel drive | |
| Three steering way | • |
| Standard tyres | 400/70-20" |
| Hydraulically controlled stabilizers | On/Off |
| Turret rotation | 415° |
| PTO (rpm) | - |
| 3-point rear linkage (kg) | _ |

NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merio dealer



MERLO S.P.A.

Via Nazionale, 9 12010 S. Defendente di Cervasca, (Cuneo) Italia Tel. +39 0171 614111

info@merlo.com www.merlo.com

Release 4/11/2025 - 8:11

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.