ADDENDUM NO. 2 TO DRAWINGS AND SPECIFICATIONS FOR THE DEKOVEN TANKS REPLACEMENT

MID-PENINSULA WATER DISTRICT SAN MATEO COUNTY, CALIFORNIA

JULY 1, 2021

NOTICE IS HEREBY GIVEN to all bidders and interested parties that the Advertisement of Proposals, Bid Proposals, Contract Documents, and Specifications of the subject project are hereby modified only insofar as the following clarifications, corrections, changes, and amendments are concerned.

The Bidder <u>MUST</u> make acknowledgement of the receipt of this addendum on Page B-10 <u>and</u> attach a copy of the addendum <u>(first page only)</u> to the Proposal section of the Contract Documents.

SITE TREES

An arborist has identified four (4) dead trees at the entrance (west side) and two (2) at the back-side (east side) at the project site. Plan C2.1 protects four (4) of the six (6) trees in the front.

The removal of the dead trees prior the start of this project has not been decided by the District as they provide screening and dust control to the site. Please bid the project as shown on the plans.

DEKOVEN DRAWINGS

Archive drawings of Dekoven Tanks are provided for information only. Dates of drawings varies. A total of five (5) sheets are included.

GENERAL PROVISION G7.22 PROPERTY INSURANCE

Revise the first sentence of the second paragraph as follows:

"Property insurance shall be on all-risk policy form (commonly known as "Builder's Risk-All"), excluding coverage for earthquakes, tsunami, *and flooding.*" Addendum No. 2 July 1, 2021 Dekoven Tanks Replacement Page 2 of 2


<u>APPENDIX – A3 MICROCLOR ON –SITE HYPCHLORITE GENERATION SYSTEM MC-300</u> UPDATED


Replace A3 with the Monoclor RCS [®] Chloramine Management System Hypochlorite and LAS Dosing with WQS & PWM400 Mixer piping and instrumentation diagram dated 6/29/2021.


Victor Fung Associate Engineer


Enclosures:

Dekoven Tanks Construction Drawings (5 Sheets) Various Dates Monoclor RCS [©] Chloramine (10 Sheets) dated 6/29/2021











ND	1999 1999 1997
EXISTING TANK EXTERIOR LADDER TO STAY	a a a a a
Existing access hatch to be removed, and hatch opening to be patched with 3/16" steel plate and built weld to existing roof plate.	540 Pice Amilie Redwood Chy. CA 5 .45/305-0472
TANK INTERIOR LADDER TO BE RELOCATED TO NEW LOCATION TO MATCH NEW ACCESS HATCH OPENING.	
REMOVE AND REPLACE EXISTING SCREEN AND RETAINING ANGLE WITH STAINLESS STEEL 6 × 8 MESH AND 1" × 1" STAINLESS STEEL ANGLE (TOTAL 4 SIDE VENT SCREENS REQUIRED FOR TANK NO. 1).	
EXISTING SIDIA, SAFETY STAND FIPE TO BE REMOVED, AND REPLACED WITH 3 - 3/4: DIA PAD EYES AND WELD TO TANKS ROOF (SEE ROOF PLAN FOR LOCATION).	
EXISTING FOOF CENTER VENT TO BE REMOVED, AND INSTALL 37 DA. ROOF VENT (SEE SHEET 3 FOR DETAIL).	
INSTALL NEW 30" DIA. MANHOLE ACROSS FROM EXISTING MANHOLE (SEE SHEET 3 FOR DETAILS).	Ē,
EXISTING ROOF VENT TO BE REMOVED WITH ROOF PLATE	
INSTALL 1/2 DIA. GALVANIZED STEEL PIPE FOR AIR TOOL, PROVIDE 80' ELBOW AT BOTH ENDS AND 1/2' BALL VALVE AT LOWER END, AND PIPE SUPPORT AT 10'C, TO C.	
PROVIDE TOOL PULLY SEE SHEET & FOR DETAIL	5
INSTALL 2: 11 DA, SCHEDULE 40 PIECS FOR CATHODIC PROTECTION WHR AND CASTIN CONCRETE TRENCH, AND OR BURGED OUTSIDE THE THENCH AT LEAST WITH 1 COVER. 3/4 DIA. ELECTRIC CONDUIT WILL BE USED FROM ROOF FOR TO CONCRETE TRENCH, PULL WIRE SHALL BE PROVIDED WITHIN PVC PIEC AND ELECTRIC CONDUIT.	A Su LT
SAND BLAST ROOF PLATE DEPRESS AREAS TO BEAR METAL AND FILL THE DEPRESS AREAS WITH EPOXY FILLER FOR TANK NO. 1.	
THE TANK OVERFLOW PIPE AND LOW LEVEL OUTLET TO LOCAL DRAIN. SYSTEM. PROVIDE NEW 6° OUTLET FOR TANK NO. 2 AND EXTEND EXISTING 6° OVERFLOW TO NEW CATCH BASIN LOCATION FOR TANK NO. 1	BNIA
NEW CATCH BASIN FOR EACH TANK, THE GRATE AND FRAME SHALL BE 2: X 2' CHRISTY 71R 420 OR APPROVED EQUAL LOCATION TO BE ADJUSTED IN FIELD.	CALFOR
INSTALL 37" DIA ROOF VENT (SEE SHEET & FOR DETAILS)	
EXISTING TANK NO. 2 HOOF PAFTER SUPPORTS, 151-BEAMS THE TO CENTER COLUMN SUPPORT PLATE.	E S
15 - INTERMEDIATE I BEAM ROOF RAFTER.	
EXISTING CATHODIC PROTECTION WIRES IN ELECTRIC CONDUCT. OR OVERHEAD WIRE TO BE REMOVED AS DIRECTED BY BELMONT COUNTY WATER DISTRICT PERSONNEL.	DISTRIC R WORK: ETAIL
PENTAGON SHAPE I BEAM BOOF SUPPORT, SUPPORTED BY FIVE COLUMNS	
EXISTING CATHODIC PROTECTION PANEL TO STAY. FILL THE CONCRETE TRENCH AT BOTH TANKS WITH 3,000 PSI CONCRETE	MATE REPA AND
EXCEPT FOR TANK OVERFLOW CATCH BASIN OR LOCATIONS AS DIRECTED BY THE ENGINEER.	AN NA
EXISTING 4"x 3" STEEL STRAP AT THE CONCRETE RING WALL FOUNDATION AT BOTH TANKS TO STAY.	
TANK NO.2 ROOF RUSTING PLATE REPAID:	18 F 5
CONTRACTOR REMOVE THE CATHODIC PROTECTION ANODES PRIOR TO REMOVE THE ENTIRE ROOF PLATE, INCLUDES ROOF VENTS ACCESS HATCH AND SAND BLASTALL ROOF SUPPORTS PRIOR TO COATING, AND INSTALL MINIMUM 3/16" NEW ROOF PLATE, CENTER ROOF VENT, ACCESS HATCH HANDRAIL, AND CUT HOLES FOR, AND REINSTALL CATHODIC PROTECTION ANDORS.	MONT OVEN TANK
PROVIDE \$/4* WELDOLET AND DRILL THROUGH AT THE SIDE OF 6* OUTLET PIPE, WITH 90° ELBOW AND 3/4* BALL VALVE.	BELMON DE KOVI TANI
PROVIDE STAUCITURE TEES WI546 AND WELDED AT BOTH ENDS TO THE ROOF PAFTER AT 4 FROM THE EDGE OF THE TANK TO PREVENT ROOF PLATE SAGENG.	
	BELMONT
	base (2/9/ accis AS SHOM Deview AL Deamt HJ Deamt HJ Deamt HJ Deams VIDEO
	التصليح المسالية والمسالية وال
	Diasiog Rupper
DEC 20 1991	2 or 3





		1			2	3			4		5		6
			LIN	IE TY	PES	T	AG	S		VA	ALVES		EQL
			<u>_</u>	<u> </u>	ELECTRICAL (AC, SINGLE PHASE)	[CHEMICAL]	<.			BB	ACTUATED VALVE (2-WAY)	\bigtriangledown	BLOWER
A		#	#		ELECTRICAL (AC, THREE PHASE)		> 1	LINE CONTINUATION TAG	G (EXTERNAL)	日路	ACTUATED VALVE (3-WAY)		CALIBRATION COLUMN
			X	-×	ELECTRICAL (DC)	[X] [#]	\rightarrow ,	LINE CONTINUATION TAG	G (INTERNAL)	₩ N	BALL VALVE BALL VALVE (3-WAY)		CALIBRATION COLOMIN
		1.12.0323.03.03	0.0311031103	CI (10 FI 1333) 1	FUTURE		AL] I	LINE IDENTIFICATION TA	G		BUTTERFLY VALVE	ħ	
			10		LIMITS		a) .	LOCAL INSTRUMENTATIO	ON TAG	Ŋ	CHECK VALVE		ELECTROLYTIC CELL
						[DESC.]	<i>.</i>			A L	CONTROL VALVE		
В					LIQUID & GAS FLOW				140		GLOBE VALVE	Ħ	
					NETWORK		PLC INSTRUMENTATION	TAG		LOCKING DRAIN VALVE		FILTER	
					SIGNAL WIRING					K	NEEDLE VALVE (2-WAY)	M>	FLOWMETER (MAGNETIC)
						[OBJECT] POWER [###] VAC, [#]6, [###]A SERVICE [(OPTION [#])]	> ı	POWER SOURCE TAG		承	NEEDLE VALVE (3-WAY)	P>	FLOWMETER (PADDLE-W
						VFD-[##	#]	VFD TAG		R	PRESSURE REGULATING VALVE	(R)	FLOWMETER (ROTAMETE
						VFD-[## [#] HP				Ŗ	PRESSURE RELIEF VALVE (2-WAY)		in dae id beenhedert noordeloo 🔭 hind hendepareereder
С			ISA	A INS	TRUMEN	IT LETTE)		*	PRESSURE RELIEF VALVE (3-WAY)		GROUNDING TARGET
		ETTER	PROCESS		MODIFIER	READOUT/OUTPUT FUNCTION		MODIFIER	1	S	SOLENOID VALVE (2-WAY)		
		A	1 N 120 N 1995 N 1	LYZER		ALARM			-	S		H	
		В	BUI	RNER		USER'S CHOICE	U	ISER'S CHOICE		S	SOLENOID VALVE (3-WAY)		ION EXCHANGE BOTTLE
		С		S CHOICE	CONTROL	CONTROL		CLOSE]				
		D		S CHOICE	DIFFERENTIAL					FITT	TINGS	\cap	
		E	A.4-140207		DATIO	PRIMARY ELEMENT			-			X	
D		F G		LOW S CHOICE	RATIO	GLASS			-	\downarrow	AIR GAP	\sim	MIXER, IMPELLER/LILY (V/
		н	1.0019020-001-0009	AND		GLASS		HIGH	-		//	\sim	
		1		RRENT		INDICATE	-		-	đþ	BULKHEAD CONNECTION	Δ	
		J	The set	OWER	SCAN				-	D	CAP	Å	MIXER, IMPELLER/LILY (VE
		к	Т	IME		CONTROL SITUATION			-	ν	0.1	/ \	
		L	LE	EVEL		LIGHT		LOW	-	Ý	DRAIN CONNECTION	-	
		м	USER'S	S CHOICE	MOMENTARY		1	NTERMEDIATE		П	FLANGE CONNECTION		
		N	USER'S	S CHOICE		USER'S CHOICE	L	ISER'S CHOICE	1	\sim	FLEX CONNECTION	\prod	MIXER, JET
E		0	USER'S	S CHOICE		ORIFICE		OPEN		0 0			
		Р	PRE	SSURE		POINT (TEST CONNECTION)				\sim	GAUGE ISOLATOR		
		Q	0.148017	ANTITY	INTEGRATE, TOTALIZE				-	\square	HOSE BARB CONNECTION	T	
		R		DIATION	RELIEF	RECORD			-	Ķ	HOSE BIBB / SPIGOT		MIXER, TANK SHARK (CIR
		S T		PEED	SAFETY	SWITCH			-	5	-		
		U		ERATURE		MULTI-FUNCTION	M	ULTI-FUNCTION	-		QUICK COUPLING	_	
		v	27836-106360-052 - 2	RATION		VALVE, DAMPER	IVI	ULTI-FUNCTION	-	D	REDUCER		
E		w		IT, FORCE		WELL			-	τĮr	UNION CONNECTION	≜	
F		x	1.27580-1.2762204194	ASSIFIED	X-AXIS	UNCLASSIFIED		JNCLASSIFIED	-				
		Y	· · · · ·	T, STATE	Y-AXIS	RELAY, COMPUTE			-	2	VENTURI INJECTOR		MIXER, TANK SHARK (SUS
		z	Sec. 4.017 PT	SITION	Z-AXIS	DRIVER, ACTUATOR, UNCL. F.C.E.]	\searrow	Y-STRAINER		
	rev. 🛆	DATE	BY		DESCRIPTION	REV. 🛆 DATE	BY		DESCRIPTION		This drawing represents an TECHNOLOGIES, INC. of sub	investment by PSI	
		06/25/21	нн		CREATED						engineering skills and experie	nce It is therefor	loaned bar A lies so
	$\overline{\bigtriangleup}$		- 6-753 104		Annual and ASTACT						without consideration other than that it is not to be used in whole or to furnish any information	e or in part to assist	in making


 \triangle

 \triangle

 \triangle

 \wedge

that it is not to be used in whole or in part to assist in making or to furnish any information to others for the making of drawings, print apparatus, or parts thereof. The acceptance of this drawing will be construed as an acceptance of the forgoing conditions and as an admission of the exclusive ownership in and to the drawings of PSI WATER TECHNOLOGIES, INC.



-
2
/

3

NOTES

1 PSI IS NOT RESPONSIBLE FOR ANY INTERCONNECTING TUBING, PIPING, FITTINGS, VALVES, ANCHORS, FASTENERS, OR SUPPORTS OF ANY KIND.

48" MINIMUM VERTICAL SEPARATION BETWEEN VENT HEADER (MEASURED AT LOW POINT) AND HYPOCHLORITE OUTLET (MEASURED AT HIGH POINT). MORE SEPARATION MAY BE NECESSARY IF HYPOCHLORITE OUTLET IS RAISED ABOVE TOP OF SKID, OR SKID IS RAISED ABOVE GROUND LEVEL.

3 BLOWER MOUNTED 24" MAXIMUM ABOVE BASE OF GENERATOR SKID.

4 BLOWER REQUIRES 39" OF STRAIGHT PIPE BEFORE ANY ELBOWS OR VALVES (FOR THIS SYSTEM'S STANDARD BLOWER)

С

D

Α

Е

REV. 🛆	DATE	BY	DESCRIPTION	Rev. \triangle	DATE	BY	DESCRIPTION	This drawing represents an investment by PSI WATER TECHNOLOGIES, INC. of substantial sums, including our	PSI V	Nater Teo	hnoloaies	PROJECT: MID-PENINSULA WA	TER DISTRICT
A	06/25/21	нн	CREATED	\square				engineering skills and experience. It is, therefore, loaned without consideration other than the agreement and condition	A UGSI S	SOLUTIONS CO	DATE:	EAST TANK & W SAN MATEO CO	EST TANK
\square				\square				that it is not to be used in whole or in part to assist in making or to furnish any information to others for the making of	and a standard or part	H. HUANG	06/25/2021	1 SUBJECT:	1970 - 664 - 1979 - 1979 August
\square				\square				drawings, print apparatus, or parts thereof. The acceptance of this drawing will be construed as an acceptance of the forgoing		ZWILLIAMS	DATE: 06/29/2021	MONOCLOF MICROCLOR MC-300 & RC	
\square				\square				conditions and as an admission of the exclusive ownership in and to the drawings of PSI WATER TECHNOLOGIES, INC.	SCALE:	N/A	SIZE:	PIPING & INSTRUMENT D DWG #: 000000-MN0003-PI	ATION DIAGRAM

7

6

8

Α


В


С

D


Ε


F








7	8	
6 9 9 c 1 1		A
2" PVC SCH80		B
2" PVC SCH80		C
	L	D
		E
		F
Ater Technologies OLUTIONS COMPANY H. HUANG DATE: 06/25/2021 DATE: 06/29/2021 SIZE: N/A D	MONOCLOR RCS	











REV. 🛆	DATE	BY	DESCRIPTION	REV. \triangle	DATE	BY	DESCRIPTION	This drawing represents an investment by PSI WATER TECHNOLOGIES, INC. of substantial sums, including our	A PSI Wa
\triangle	06/25/21	нн	CREATED	\square				engineering skills and experience. It is, therefore, loaned without consideration other than the agreement and condition	A UGSI SOL
\square				\square				or to furnish any information to others for the making	
\square				\square				drawings, print apparatus, or parts thereof. The acceptance of this drawing will be construed as an acceptance of the forgoing	Z
\square				$ \Delta $				conditions and as an admission of the exclusive ownership in and to the drawings of PSI WATER TECHNOLOGIES, INC.	SCALE: