



VANO WING SP DALI

Wall-mounted light grey 25W 1400lm 3000K CRI80
120° DALI

The aluminium and glass VANO WING SP DALI outdoor spotlight is perfect for professional surface, display and advertising sign lighting. It can also be controlled and dimmed using DALI. Surface illumination can be achieved even with minimal spacing thanks to the wide beam angle of 120 degrees and the asymmetric reflector. The warm white light (3000 K) offers excellent intensity thanks to a luminous flux of 1400 lumen. Thanks to its IP65 protection class rating, this spotlight is ideally protected against moisture penetration. And the integrated ballast makes it quick and easy to connect to the mains.

TECHNICAL DATA

| | |
|-----------------------------------|---------------------|
| Item no. | 1006268 |
| Number of different light outlets | 1 |
| Rotating or tilting | tiltable |
| IP Code | IP 65 |
| Impact resistance class | IK 06 |
| Impact resistance | 0.2 Joule |
| Assembly | Surface |
| Assembly details | Ceiling,Ground,Wall |
| Dimmable | Yes |
| Dimming technology | DALI |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 500 mA |
| Safety class | I |
| Wattage | 25 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Network rated standby power | 0.3 W |
| Level of inrush current | 16.5 A |
| Duration of inrush current | 180 µs |
| Stroboscopic effect (SVM) | 0.01 |
| Lumen | 1400 lm |
| Colour temperature | 3000 Kelvin |

Light Source

1319287



| | |
|--------------------|-----------|
| Beam angle | 120 ° |
| Color | grey |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 50000 h |
| Light distribution | symmetric |
| Light outlet | direct |
| Risk Group | 0 |
| Width | 63.5 cm |
| Height | 6.5 cm |
| Depth | 20.5 cm |
| Net weight | 3.29 kg |
| Gross weight | 3.52 kg |