



## OCULUS WL PHASE

Wall-mounted light white 8.5W 570lm 2000-3000K  
CRI90 100° Dimmable

The OCULUS WL PHASE wall light emits a sharply delineated beam of light thanks to its special lens technology. This cylindrical aluminium and glass light also creates particularly welcoming illumination thanks to its high CRI of over 90 and the dim-to-warm function (2000-3000K). Ideal for GP practices, law offices, cafés, hotels, restaurants and the private sector. Establishing a simple, direct connection to a 220 volt mains supply is incredibly straightforward.

## TECHNICAL DATA

|                                   |                   |
|-----------------------------------|-------------------|
| Item no.                          | 1006308           |
| Number of different light outlets | 1                 |
| IP Code                           | IP 20             |
| Assembly                          | Surface           |
| Assembly details                  | Wall              |
| Dimmable                          | Yes               |
| Dimming technology                | trailing edge     |
| Primary nominal voltage           | 220-240V ~50/60Hz |
| Secondary power / voltage         | 350 mA            |
| Safety class                      | I                 |
| Wattage                           | 8.5 W             |
| Minimum ambient temperature       | -20 °C            |
| Maximum ambient temperature       | 45 °C             |
| Level of inrush current           | 2 A               |
| Duration of inrush current        | 50 µs             |
| Stroboscopic effect (SVM)         | 0.03              |
| Lumen                             | 570 lm            |
| Colour temperature                | 2000-3000 Kelvin  |
| Beam angle                        | 100 °             |
| Color                             | white             |
| CRI                               | 90                |
| LXXBXX data                       | L70B50            |

## Light Source

|        |   |
|--------|---|
| 916398 |  |
|--------|---|

|              |          |
|--------------|----------|
| Service life | 25000 h  |
| Risk Group   | 1        |
| Height       | 8.75 cm  |
| Depth        | 12.4 cm  |
| Diameter     | 9 cm     |
| Net weight   | 0.63 kg  |
| Gross weight | 0.674 kg |