



## ENOLA OCULUS CL

Ceiling-mounted light anthracite 11W 1000/1100lm  
3000/4000K CRI90 100°

Minimalist design with a sharply delineated light: the cylindrical ENOLA OCULUS CL uses special lens technology, which makes it the perfect accent lighting source. At the same time, this aluminium and glass ceiling light can withstand dirt and jets of water from all angles thanks to its IP65 protection class rating. The light colour (3000/4000K) in this 1000 / 1100 lumen outdoor light can be adjusted using the CCT switch before installation. The ENOLA OCULUS CL also has impressive characteristics such as a CRI of over 90 and an installation panel (supplied with the light) that enables a quick connection to a 220 volt supply.

## TECHNICAL DATA

Item no.	1006327
IP Code	IP 65
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Assembly	Surface
Assembly details	Ceiling, Ceiling with Acc.
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	11 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Level of inrush current	4.7 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.01
Lumen	1000 / 1100 lm
Colour temperature	3000/4000 Kelvin
Beam angle	100 °
Color	anthracite
CRI	90
LXXBXX data	L70B50
Service life	30000 h

## Light Source

916566	
--------	---

## Accessories

1003479	Spacer set , for the ENO-LA SQUARE OUT and ROUND OUT ceiling lights in anthracite
---------	---

Risk Group	1
Height	12 cm
Diameter	10 cm
Net weight	0.758 kg
Gross weight	0.951 kg