



WORKLIGHT FL

Free-standing lamp silver 79W 7600lm 4000K CRI80 80°

The silver WORKLIGHT FL can handle any requirements for modern workplace lighting. Thanks to the integrated LED light, 7600 lumen, UGR ≤ 19 and 4000 Kelvin, this free-standing lamp emits a neutral white, glare-free light that boosts concentration. Other features include a motion sensor, daylight control and full dimming control. Thanks to the integrated driver and supply cable, including plug, the WORKLIGHT FL can be connected directly. With an LED lifespan of 50,000 hours, it is also exceptionally durable.

TECHNICAL DATA

Item no.	1006343
Number of different light outlets	2
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Mobile
Dimmable	Yes
Dimming technology	Touch
Primary nominal voltage	200-240V ~50/60Hz
Secondary power / voltage	2000 mA
Safety class	I
Wattage	79 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
	100
Level of inrush current	30 A
Level of inrush current	30 A
Level of inrush current Duration of inrush current	30 A 150 μs
Level of inrush current Duration of inrush current Stroboscopic effect (SVM)	30 A 150 μs
Level of inrush current Duration of inrush current Stroboscopic effect (SVM) Lumen	30 A 150 μs 0 7600 lm
Level of inrush current Duration of inrush current Stroboscopic effect (SVM) Lumen Colour temperature	30 A 150 μs 0 7600 lm 4000 Kelvin
Level of inrush current Duration of inrush current Stroboscopic effect (SVM) Lumen Colour temperature Beam angle	30 A 150 μs 0 7600 lm 4000 Kelvin 80 °



Light Source

916336

UGR≤	19
LXXBXX data	L80B10
Service life	50000 h
Risk Group	0
Length	69.2 cm
Width	31 cm
Height	195 cm
Net weight	17.1 kg
Gross weight	18.297 kg