



M-POL 90 Pole

Bollard, anthracite, 83.4cm

DALI-compatible bollard light for professional outdoor projects: the aluminium M-POL 90 Pole can be dimmed and controlled via the digital interface. Variable lamp heads and diffusers ensure a wide range of applications. The colour temperature (2700/3000K) can be selected via the CCT switch before installation. Thanks to its IP65 protection class rating, this anthracite bollard light is protected against jets of water from all directions. To ensure it can withstand heavy impacts, it has an IK10 impact rating. Easy installation via the connection box is entirely straightforward.

TECHNICAL DATA

Item no.	1006381
Color	anthracite
Height	83.4 cm
Diameter	12.4 cm
Net weight	2.842 kg
Gross weight	3.041 kg

Accessories

1006382	M-POL ground anchor , stainless steel
1006383	M-POL M Polehead , Lamp head, anthracite, 11W, 470/510lm, 2700/3000K, CRI90
1006384	M-POL M Polehead , Lamp head, anthracite, 11W, 590/660lm, 2700/3000K, CRI90
1006385	M-POL S Polehead , Lou- ver lamp head, anthra- cite, 11W, 145/155lm, 2700/3000K, CRI90
1006386	M-POL M Polehead , Louver lamp head, an- thracite, 11W, 190/210lm, 2700/3000K, CRI90
1006387	M-POL S Polehead , Shader lamp head, an- thracite, 11W, 285/310lm, 2700/3000K, CRI90
1006388	M-POL M Polehead , Shader lamp head, an- thracite, 11W, 420/460lm, 2700/3000K, CRI90
1006389	M-POL S Polehead , Lamp head, anthracite, 19W, 890/950lm, 2700/3000K, CRI90, DA- LI
1006390	M-POL M Polehead , Lamp head, anthracite, 19W, 1150/1230lm, 2700/3000K, CRI90, DA- LI
1006391	M-POL S Polehead , Lou- ver lamp head, anthra- cite, 19W, 260/270lm, 2700/3000K, CRI90, DA- LI
1006392	M-POL M Polehead , Louver lamp head, an- thracite, 19W, 350/370lm, 2700/3000K, CRI90, DA- LI

1006393	M-POL S Polehead , Shader lamp head, an- thracite, 19W, 520/550lm, 2700/3000K, CRI90, DA- LI
1006394	M-POL M Polehead , Shader lamp head, an- thracite, 19W, 820/870lm, 2700/3000K, CRI90, DA- LI
1006453	Connection box , 5-pin, IP68, black, DALI
228726	T-CONNECTION BOX , black, IP68
228730	CONNECTION BOX , 3-pin, IP68