




## M-POL M Polehead

Louver lamp head, anthracite, 19W, 350/370lm, 2700/3000K, CRI90, DALI

Suitable for universal use, featuring a sophisticated design and high output: the lamp heads and diffusers in the first DALI-dimmable SLV outdoor family are ideal for a variety of applications. The cylindrical M-POL M Polehead has a CRI of over 90, 350 / 370 lumen, and an LED lifespan of 50,000 hours, which can satisfy the most challenging lighting design requirements. Enjoy the flexibility to implement a diverse range of lighting projects.



## TECHNICAL DATA

Item no.	1006392
IP Code	IP 65
Impact resistance class	IK 10
Assembly details	Ground with Acc.
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500
Wattage	19 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Rated standby power	0.5 W
Level of inrush current	10 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.01
Lumen	350 / 370 lm
Colour temperature	2700/3000 Kelvin
Color	anthracite
CRI	90
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1

## Light Source



## Accessories

1006379	M-POL 30 Pole , Bollard, anthracite, 23.4cm
1006380	M-POL 60 Pole , Bollard, anthracite, 53.4cm
1006381	M-POL 90 Pole , Bollard, anthracite, 83.4cm
1006382	M-POL ground anchor , stainless steel
1006453	Connection box , 5-pin, IP68, black, DALI
228725	CONNECTION BOX , 5-pin, IP68

Height	26.4 cm
Diameter	12.26 cm
Net weight	1.806 kg
Gross weight	1.932 kg