



## MANA BASE WL PHASE


Wall-mounted light anthracite round 15W 800/820lm  
 2700/3000K CRI90 Dimmable

The MANA BASE WL PHASE wall light is dimmable and designed with a high-performance LED, which allows configuration of the colour temperature before installation (2700/3000K). Thanks to its IP65 protection class rating, this aluminium and polycarbonate (PC) outdoor light is protected in any weather. With a CRI of over 90, colours have a natural appearance. It is quick and easy to establish a direct connection to a 220 volt supply. Please note, the MANA BASE WL PHASE must be combined with the matching MANA shade.

## TECHNICAL DATA

Item no.	1006319
IP Code	IP 65
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	68
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	15 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	14 A
Duration of inrush current	8.5 µs
Stroboscopic effect (SVM)	0.1
Lumen	800 / 820 lm
Colour temperature	2700/3000 Kelvin
Color	anthracite
CRI	90
LXXBXX data	L80B50
Service life	50000 h

## Light Source

916354		<b>Risk Group</b>	1
		<b>Height</b>	9 cm
		<b>Diameter</b>	10 cm
		<b>Net weight</b>	0.5 kg
		<b>Gross weight</b>	0.535 kg