




M-POL M Polehead

Louver lamp head, anthracite, 19W, 350/370lm, 2700/3000K, CRI90, DALI

Suitable for universal use, featuring a sophisticated design and high output: the lamp heads and diffusers in the first DALI-dimmable SLV outdoor family are ideal for a variety of applications. The cylindrical M-POL M Polehead has a CRI of over 90, 350 / 370 lumen, and an LED lifespan of 50,000 hours, which can satisfy the most challenging lighting design requirements. Enjoy the flexibility to implement a diverse range of lighting projects.



TECHNICAL DATA

Item no.	1006392
IP Code	IP 65
Impact resistance class	IK 10
Assembly details	Ground with Acc.
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500
Wattage	19 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Rated standby power	0.5 W
Level of inrush current	10 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.01
Lumen	350 / 370 lm
Colour temperature	2700/3000 Kelvin
Color	anthracite
CRI	90
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1

Light Source

	
--	---

Accessories

1006379	M-POL 30 Pole , Bollard, anthracite, 23.4cm
1006380	M-POL 60 Pole , Bollard, anthracite, 53.4cm
1006381	M-POL 90 Pole , Bollard, anthracite, 83.4cm
1006382	M-POL ground anchor , stainless steel
1006453	Connection box , 5-pin, IP68, black, DALI
228725	CONNECTION BOX , 5-pin, IP68

Height	26.4 cm
Diameter	12.26 cm
Net weight	1.806 kg
Gross weight	1.932 kg