

Discrete Element Modelling (DEM) on a System Level

Generating ROMs with Rocky DEM and ANSYS

Presented by:

Wynand Prinsloo

Agenda



- Introduction (What\Why ROM)
- Example Case Background
- ROM Setup
- ROM Results & Validation
- Shortfalls
- Where To Next

Q&A





- ROM = Reduced Order Model
- What: Mathematical representation of physics system.
- Why: Estimate results in continuous space by using quick equations instead of doing full physics solve.
- Process: Design of Experiments > Response
 Surface Generation > ROM Export



- ANSYS can be a powerful tool in generating ROMs and digital twins.
- Structural, Fluid and Emag ROMs covered by ANSYS.
- What about bulk flow applications?




- ANSYS can be a powerful tool in generating ROMs and digital twins.
- Structural, Fluid and Emag twins covered by ANSYS.
- What about bulk flow applications?



 Rocky integrates into ANSYS DesignXplorer (DX).


 This enables the generation of ROMs/digital twins for bulk flow applications.








 Real world test case: Shuttle cars offloading to a feeder.






 Concern: Restriction on mass flow from feeder.










Outflow affected by many variables:





- DEM answer:
 - Accurate answer.
 - New solve for each set of inputs.
 - Good for system with fixed inputs.
- ROM answer:
 - Estimated answer.
 - Instant answer for any inputs.
 - More favourable for highly variable system.




ROM Setup

ROM Strategy




Separate ROMs for shuttle cars and feeder:



ROM Strategy



- Separate ROMs for shuttle cars and feeder:
 - Allows for easy expansion of model.




ROM Setup



• Shuttle car setup:

20 tons of material.

Different conveyor speeds tested.




Shuttle Car ROM



- Shuttle car response surface:
 - Inputs:
 - Conveyor speed
 - Mass in car


- Output:
 - Mass flow from car



Shuttle Car ROM



Shuttle car in ANSYS Twin Builder




Shuttle Car ROM Results



Particle mass in shuttle

Mass flow from shuttle






Feeder setup:


Flow into feeder.

Different conveyor speeds tested.






- Feeder response surface:
 - Inputs:
 - Conveyor speed
 - Mass in feeder
 - Output:
 - Mass flow from feeder






• Feeder response surface:

- Inputs:
 - Conveyor speed
 - Time
- Output:
 - Mass flow from feeder






Feeder in ANSYS Twin Builder



ROM Setup



Feeder in ANSYS Twin Builder






ROM Results & Validation

Feeder ROM Results



Particle mass in feeder:

Mass flow from feeder:



ROM Validation



Validation Case:

2 x 20 ton Shuttle cars at a conveyor speed of 0.35 m/s.


- Feeder with conveyor speed at 0.46m/s.

ROM Validation



• Simulation results:






ROM Validation



Result comparison:








Shortfalls

Shortfalls




- DEM solving time can cause DOE generation to take large amounts of time:
 - GPU solving capabilities and advancing GPU technologies improve this issue.



Shortfalls

- OFINSOFT
- Sensitive to response surface type.
 - It is quick to test the effectiveness of different response surface types with ANSYS DX and Twin Builder.



Where To Now



- Use ROM to predict effects of system changes.
- Modify ROM to include calculation of spilled mass.
- Use ROM to optimize the system.
- Link to IOT platform to predict overloading, damage and spillage.
- Use ROM in PLC to automate conveyor speeds.