



Pinout		
Signal	CON A	
+	+	RED
-	-	GREEN

Label Specification (Item 5)	
Text	103-1
Text Color	Black
Label Color	Silver or White
Label Width	9mm +/- 2mm
Label Length	40mm +/- 4mm

Note 1c: "+" split pins exist on genuine AMASS products.

Note 4: Heatshrink (Item #4) must be pushed into connector housing to sit on this inner ledge (~1mm deep) before heating. Units with heatshrink on the outside of the housing body are to be rejected.

PARTS LIST (NO SUBSTITUTIONS FOR LISTED MPNs UNLESS APPROVED BY MODALAI)

ITEM #	DESCRIPTION	MPN	QTY
1	CON A: AMASS, MALE PANEL MOUNT PLUG, 2-POS, BLACK	XT60EW-M	1
2	18AWG Silicone Wire, GREEN, 80mm		1
3	18AWG Silicone Wire, RED, 80mm		1
4	Silicon Heatshrink (10mm x2) with inner diameter adhesive, applied to terminals where noted, see important notes about rejects.		Qty-2 10mm
5	Label, see label specs above		1

https://www.modalai.com/	Design Copyright by ModalAI, INC.	Approved by HW_ENG
	Document type NF_CABLE_DWG	Document status
	Title XT60EW-M Male Plug BULKHEAD Mount, Red/Green, 80mm	DWG No. MCBL-00103-1
	Rev. A	Revision Date 03/01/2024