

Short-stroke cylinder AEVC-50-10-I-P

Part number: 188254

FESTO



 General operating condition

Data sheet

| Feature | Value |
|--|--|
| Stroke | 10 mm |
| Piston diameter | 50 mm |
| Spring return force with retracted piston rod | 40 N |
| Based on standard | ISO 6431 Hole pattern VDMA 24562 |
| Cushioning | Elastic cushioning rings/plates at both ends |
| Mounting position | optional |
| Mode of operation | Pushing Single-acting |
| Design | Piston Piston rod |
| Position detection | Without |
| Symbol | 00991730 |
| Operating pressure | 0.1 MPa ... 1 MPa |
| Operating pressure | 1 bar ... 10 bar |
| Operating pressure | 14.5 psi ... 145 psi |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC | 1 - Low corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Ambient temperature | -20 °C ... 80 °C |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke | 1118 N |
| Moving mass | 105 g |
| Product weight | 271 g |
| Type of mounting | With through-hole With accessories |
| Pneumatic connection | G1/8 |
| Note on materials | RoHS-compliant |
| Material cover | Wrought aluminium alloy Anodised |
| Material seals | NBR TPE-U(PU) |
| Material housing | Anodised |
| Material piston rod | High-alloy steel |