

Image may differ from product. See specification for details.

# 23222 CCK/W33

## Spherical roller bearing with tapered bore and relubrication features

Spherical roller bearings can accommodate heavy loads in both directions. They are self-aligning and accommodate misalignment and shaft deflections, with virtually no increase in friction or temperature. The design includes features to facilitate relubrication. The bearings can be used in a modular system, including housings, sleeves and nuts.

- Accommodate misalignment
- High load carrying capacity
- Relubrication features
- Low friction and long service life
- Increased wear resistance

# Overview

## Dimensions

| | |
|---|---|
| Bore diameter | 4.3307 in |
| Outside diameter | 7.874 in |
| Width | 2.748 in |

## Performance

| | |
|---|---|
| Basic dynamic load rating | 140 730 lbf |
| Basic static load rating | 171 979 lbf |
| Reference speed | 2 200 r/min |
| Limiting speed | 3 200 r/min |
| SKF performance class | SKF Explorer |

## Properties


| | |
|---|---|
| Number of rows | 2 |
| Locating feature, bearing outer ring | Without |
| Bore type | Tapered 1:12 |
| Cage | Sheet metal |
| Radial internal clearance | CN |
| Tolerance class for dimensions | Normal |
| Tolerance class for run-out | P5 |
| Sealing | Without |
| Lubricant | None |
| Relubrication feature | With |
| Candidate for remanufacturing | Yes |
| Indicative carbon footprint for new product | 73.6 lb $CO_2$e |
| Indicative carbon footprint for remanufactured product | 25.8 lb $CO_2$e |

## Logistics

| | |
|---|---|
| Product net weight | 20.4 lb |
| eClass code | 23-05-09-11 |
| UNSPSC code | 31171510 |


# Technical specification

| | |
|---|---|
| Bore type | Tapered 1:12 |




## Dimensions

| | | |
|---|---|---|
| d | 4.3307 in | Bore diameter |
| $t_{\Delta dmp}$ | 0 – 35 µm | Deviation limits of mid-range bore diameter |
| $t_{\Delta SL}$ | 0 – 35 µm | Deviation limits of tapered slope |
| D | 7.874 in | Outside diameter |
| $t_{\Delta Dmp}$ | -30 – 0 µm | Deviation limits of mid-range outside diameter |
| B | 2.748 in | Width |
| $t_{\Delta Bs}$ | -80 – 0 µm | Deviation limits of ring width |
| $d_2$ | ≈ 5.1181 in | Shoulder diameter of inner ring |
| $D_1$ | ≈ 6.6535 in | Shoulder/recess diameter of outer ring |
| b | 0.3268 in | Width of lubrication groove |
| K | 0.1772 in | Diameter of lubrication hole |
| $r_{1,2}$ | min. 0.0827 in | Chamfer dimension |
| | Normal | ISO tolerance class for dimensions |




## Abutment dimensions

| | | |
|---|---|---|
| $D_a$ | max. 7.4016 in | Diameter of housing abutment |
| $r_a$ | max. 0.0787 in | Radius of fillet |

## Calculation data

| | | |
|---|---|---|
| SKF performance class | | SKF Explorer |
| Basic dynamic load rating | C | 140 730 lbf |
| Basic static load rating | $C_0$ | 171 979 lbf |
| Fatigue load limit | $P_u$ | 17 198 lbf |
| Reference speed | | 2 200 r/min |
| Limiting speed | | 3 200 r/min |
| Limiting value | e | 0.33 |
| Calculation factor | $Y_1$ | 2 |
| Calculation factor | $Y_2$ | 3 |
| Calculation factor | $Y_0$ | 2 |

## Tolerances of run-out

| | | |
|---|---|---|
| Range of section height at inner ring of assembled bearing | $t_{Kia}$ | 6 µm |
| Maximum run-out of inner ring side face to the bore | $t_{Sd}$ | 9 µm |
| Range of section height at outer ring of assembled bearing | $t_{Kea}$ | 15 µm |
| Perpendicularity of outer ring outside surface | $t_{SD}$ | 5.5 µm |
| ISO tolerance class for geometrical tolerances | | P5 |

## Radial internal clearance

| | |
|---|---|
| Minimum initial clearance | 0.0039 in |
| Maximum initial clearance | 0.0053 in |

## Tolerances and clearances

### GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal, P6, P5, tapered bore 1:12, tapered bore 1:30
- Radial internal clearance: cylindrical bore, tapered bore

### BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit

# Compatible products

## Recommended product

| | |
|---|---|
| Withdrawal sleeve, basic design, ISO standards | AHX 3222 G |
| Adapter sleeve with KM lock nut and MB lock washer, metric dimensions | H 2322 |
| Adapter sleeve with KMFE lock nut, metric dimensions | H 2322 E |
| Adapter sleeve with KM lock nut and MB lock washer, metric dimensions with inch bore | HE 2322 |
| Adapter sleeve with AN or N lock nut and W lock washer, inch dimensions | SNW 122X3.15/16 |

## More Information

### Product details

- Designs and variants
- General bearing specifications
- Loads
- Temperature limits
- Permissible speed
- Design considerations
- Mounting
- Designation system

### Engineering information

- Principles of rolling bearing selection
- General bearing knowledge
- Bearing selection process
- Bearing failure and how to prevent it

### Tools

- SimPro Quick
- SKF Product select - Select and evaluate bearing
- SKF Product select - Combine housing with bearing
- LubeSelect for SKF greases
- Drive-up Method Program
- Heater selection tool
- Oil Injection Method Program
- Tool and Accessory Selector for sleeves and shafts

# Terms of use

By accessing and using this website / app owned and published by AB SKF (publ.) (556007-3495 · Gothenburg) (“SKF”), you agree to the following terms and conditions:

### Warranty Disclaimer and Limitation of Liability

Although every care has been taken to assure the accuracy of the information on this website / app, SKF provides this information "AS IS" and DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. You acknowledge that your use of this website / app is at your sole risk, that you assume full responsibility for all costs associated with use of this website / app, and that SKF shall not be liable for any direct, incidental, consequential, or indirect damages of any kind arising out of your access to, or use of the information or software made available on this website / app.

Any warranties and representations in this website / app for SKF products or services that you purchase or use will be subject to the agreed upon terms and conditions in the contract for such product or service.

Further, for non-SKF websites / apps that are referenced in our website / app or where a hyperlink appears, SKF makes no warranties concerning the accuracy or reliability of the information in these websites / apps and assumes no responsibility for material created or published by third parties contained therein. In addition, SKF does not warrant that this website / app or these other linked websites / apps are free from viruses or other harmful elements.

### Third Party Services

When viewing YouTube content via the SKF website(s) (i.e. using YouTube API Services), you agree to be bound by the YouTube Terms of Service.

### Copyright

Copyright in this website / app copyright of the information and software made available on this website / app rest with SKF or its licensors. All rights are reserved. All licensed material will reference the licensor that has granted SKF the right to use the material. The information and software made available on this website / app may not be reproduced, duplicated, copied, transferred, distributed, stored, modified, downloaded or otherwise exploited for any commercial use without the prior written approval of SKF. However, it may be reproduced, stored and downloaded for use by individuals without prior written approval of SKF. Under no circumstances may this information or software be supplied to third parties.

This website /app includes certain images used under license from Shutterstock, Inc.

### Trademarks and Patents

All trademarks, brand names, and corporate logos displayed on the website / app are the property of SKF or its licensors, and may not be used in any way without prior written approval by SKF. All licensed trademarks published on this website / app reference the licensor that has granted SKF the right to use the trademark. Access to this website / app does not grant to the user any license under any patents owned by or licensed to SKF.

### Changes

SKF reserves the right to make changes or additions to this website / app at any time.