



Image may differ from product. See specification for details.

## 23232 CC/W33

### Spherical roller bearing with relubrication features

Spherical roller bearings can accommodate heavy loads in both directions. They are self-aligning and accommodate misalignment and shaft deflections, with virtually no increase in friction or temperature. The design includes features to facilitate relubrication. The bearings can be used in a modular system, including housings, sleeves and nuts.

- Accommodate misalignment
- High load carrying capacity
- Relubrication features
- Low friction and long service life
- Increased wear resistance

Overview

Dimensions

|                  |            |
|------------------|------------|
| Bore diameter    | 6.2992 in  |
| Outside diameter | 11.4173 in |
| Width            | 4.0945 in  |

Performance

|                           |              |
|---------------------------|--------------|
| Basic dynamic load rating | 287 980 lbf  |
| Basic static load rating  | 373 183 lbf  |
| Reference speed           | 1 500 r/min  |
| Limiting speed            | 2 200 r/min  |
| SKF performance class     | SKF Explorer |


Properties

|                                                        |                           |
|--------------------------------------------------------|---------------------------|
| Number of rows                                         | 2                         |
| Locating feature, bearing outer ring                   | Without                   |
| Bore type                                              | Cylindrical               |
| Cage                                                   | Sheet metal               |
| Radial internal clearance                              | CN                        |
| Tolerance class for dimensions                         | Normal                    |
| Tolerance class for run-out                            | P5                        |
| Sealing                                                | Without                   |
| Lubricant                                              | None                      |
| Relubrication feature                                  | With                      |
| Candidate for remanufacturing                          | Yes                       |
| Indicative carbon footprint for new product            | 231 lb CO <sub>2</sub> e  |
| Indicative carbon footprint for remanufactured product | 80.9 lb CO <sub>2</sub> e |

Logistics


|                    |             |
|--------------------|-------------|
| Product net weight | 64.2 lb     |
| eClass code        | 23-05-09-11 |
| UNSPSC code        | 31171510    |

Technical specification



Dimensions

|                   |                |                                                |
|-------------------|----------------|------------------------------------------------|
| d                 | 6.2992 in      | Bore diameter                                  |
| t <sub>Δdmp</sub> | -25 – 0 μm     | Deviation limits of mid-range bore diameter    |
| D                 | 11.4173 in     | Outside diameter                               |
| t <sub>ΔDmp</sub> | -35 – 0 μm     | Deviation limits of mid-range outside diameter |
| B                 | 4.0945 in      | Width                                          |
| t <sub>ΔBs</sub>  | -80 – 0 μm     | Deviation limits of ring width                 |
| d <sub>2</sub>    | ≈ 7.4016 in    | Shoulder diameter of inner ring                |
| D <sub>1</sub>    | ≈ 9.6063 in    | Shoulder/recess diameter of outer ring         |
| b                 | 0.5472 in      | Width of lubrication groove                    |
| K                 | 0.2953 in      | Diameter of lubrication hole                   |
| r <sub>1,2</sub>  | min. 0.1181 in | Chamfer dimension                              |
|                   | Normal         | ISO tolerance class for dimensions             |



Abutment dimensions

|                |                 |                              |
|----------------|-----------------|------------------------------|
| d <sub>a</sub> | min. 6.8504 in  | Diameter of shaft abutment   |
| D <sub>a</sub> | max. 10.8661 in | Diameter of housing abutment |
| r <sub>a</sub> | max. 0.0984 in  | Radius of fillet             |

Calculation data

|                           |                |              |
|---------------------------|----------------|--------------|
| SKF performance class     |                | SKF Explorer |
| Basic dynamic load rating | C              | 287 980 lbf  |
| Basic static load rating  | C <sub>0</sub> | 373 183 lbf  |
| Fatigue load limit        | P <sub>u</sub> | 34 396 lbf   |
| Reference speed           |                | 1 500 r/min  |
| Limiting speed            |                | 2 200 r/min  |
| Limiting value            | e              | 0.35         |
| Calculation factor        | Y <sub>1</sub> | 1.9          |
| Calculation factor        | Y <sub>2</sub> | 2.9          |
| Calculation factor        | Y <sub>0</sub> | 1.8          |

Tolerances of run-out

|                                                            |                  |        |
|------------------------------------------------------------|------------------|--------|
| Range of section height at inner ring of assembled bearing | t <sub>Kia</sub> | 8 μm   |
| Maximum run-out of inner ring side face to the bore        | t <sub>Sd</sub>  | 10 μm  |
| Range of section height at outer ring of assembled bearing | t <sub>Kea</sub> | 18 μm  |
| Perpendicularity of outer ring outside surface             | t <sub>SD</sub>  | 6.5 μm |
| ISO tolerance class for geometrical tolerances             |                  | P5     |

Radial internal clearance

|                           |           |
|---------------------------|-----------|
| Minimum initial clearance | 0.0043 in |
| Maximum initial clearance | 0.0067 in |

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal, P6, P5, tapered bore 1:12, tapered bore 1:30
- Radial internal clearance: cylindrical bore, tapered bore

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit



More Information

| Product details                                | Engineering information                                 | Tools                                                              |
|------------------------------------------------|---------------------------------------------------------|--------------------------------------------------------------------|
| <a href="#">Designs and variants</a>           | <a href="#">Principles of rolling bearing selection</a> | <a href="#">SimPro Quick</a>                                       |
| <a href="#">General bearing specifications</a> | <a href="#">General bearing knowledge</a>               | <a href="#">SKF Product select - Select and evaluate bearing</a>   |
| <a href="#">Loads</a>                          | <a href="#">Bearing selection process</a>               | <a href="#">SKF Product select - Combine housing with bearing</a>  |
| <a href="#">Temperature limits</a>             | <a href="#">Bearing failure and how to prevent it</a>   | <a href="#">LubeSelect for SKF greases</a>                         |
| <a href="#">Permissible speed</a>              |                                                         | <a href="#">Drive-up Method Program</a>                            |
| <a href="#">Design considerations</a>          |                                                         | <a href="#">Heater selection tool</a>                              |
| <a href="#">Mounting</a>                       |                                                         | <a href="#">Oil Injection Method Program</a>                       |
| <a href="#">Designation system</a>             |                                                         | <a href="#">Tool and Accessory Selector for sleeves and shafts</a> |
|                                                |                                                         |                                                                    |



# Terms of use

By accessing and using this website / app owned and published by AB SKF (publ.) (556007-3495 · Gothenburg) ("SKF"), you agree to the following terms and conditions:

## **Warranty Disclaimer and Limitation of Liability**

Although every care has been taken to assure the accuracy of the information on this website / app, SKF provides this information "AS IS" and DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. You acknowledge that your use of this website / app is at your sole risk, that you assume full responsibility for all costs associated with use of this website / app, and that SKF shall not be liable for any direct, incidental, consequential, or indirect damages of any kind arising out of your access to, or use of the information or software made available on this website / app.

Any warranties and representations in this website / app for SKF products or services that you purchase or use will be subject to the agreed upon terms and conditions in the contract for such product or service.

Further, for non-SKF websites / apps that are referenced in our website / app or where a hyperlink appears, SKF makes no warranties concerning the accuracy or reliability of the information in these websites / apps and assumes no responsibility for material created or published by third parties contained therein. In addition, SKF does not warrant that this website / app or these other linked websites / apps are free from viruses or other harmful elements.

## **Third Party Services**

When viewing YouTube content via the SKF website(s) (i.e. using [YouTube API Services](#)), you agree to be bound by the [YouTube Terms of Service](#).

## **Copyright**

Copyright in this website / app copyright of the information and software made available on this website / app rest with SKF or its licensors. All rights are reserved. All licensed material will reference the licensor that has granted SKF the right to use the material. The information and software made available on this website / app may not be reproduced, duplicated, copied, transferred, distributed, stored, modified, downloaded or otherwise exploited for any commercial use without the prior written approval of SKF. However, it may be reproduced, stored and downloaded for use by individuals without prior written approval of SKF. Under no circumstances may this information or software be supplied to third parties.

This website /app includes certain images used under license from Shutterstock, Inc.

## **Trademarks and Patents**

All trademarks, brand names, and corporate logos displayed on the website / app are the property of SKF or its licensors, and may not be used in any way without prior written approval by SKF. All licensed trademarks published on this website / app reference the licensor that has granted SKF the right to use the trademark. Access to this website / app does not grant to the user any license under any patents owned by or licensed to SKF.

## **Changes**

SKF reserves the right to make changes or additions to this website / app at any time.