


The Timken Company

4500 Mt Pleasant St. NW


N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number 23140EJW33C3, Spherical Roller Bearings - Steel Cage

Spherical bearings are designed to manage high radial loads even when misalignment, poor lubrication, contamination, extreme speeds or critical application stresses are present.



[Specifications](#) | [Factors](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#)

Specifications

UPC Code	087796312951
Design Unit	Metric
d - Bore	200 mm
Lubrication Type	Standard Grease
Cage Type	EJ
Cage Material	Steel
Superseded Part	23140CJW33C3

Factors


 e - ISO Factor¹

0.31

Y0 - ISO Factor²	2.1
Y1 - ISO Factor³	2.15
Y2 - ISO Factor⁴	3.2
Reference Thermal Speed Rating (Grease)	1200 rpm
Reference Thermal Speed Rating (Oil)⁵	1400 rpm
Cg - Geometry Factor⁶	0.0978

Dimensions

D - Outer Diameter	340 mm 13.3858 in
B' - Inner Ring Width	112 mm 4.4094 in
B - Outer Ring Width	112 mm 4.4094 in

Abutment and Fillet Dimensions

R - Inner Ring "To Clear" Radius⁷	2.5 mm 0.100 in
r - Outer Ring "To Clear" Radius⁸	2.5 mm 0.1 in
da - Inner Ring Backing Diameter	230 mm 9.0000 in
Da - Outer Ring Backing Diameter	308 mm 12.1000 in

Basic Load Ratings

C0 - Static Radial Rating	2290000 N 514000 lbf
C1(2) - Dynamic Radial Rating (Two-Rows)	1660000 N 373000 lbf

¹ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

² These factors apply for both inch and metric calculations. See engineering

³ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.


⁴ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁵ See thermal speed ratings in the engineering section.

⁶ Geometry constant for Lubrication Life Adjustment Factor a_3 .


⁷ Maximum housing fillet radius that bearing corners will clear.

⁸ These maximum fillet radii will be cleared by the bearing corners.



METRIC UNITS

Number of Rollers Per Row	20
ISO Factor e	0.31
ISO Factor Y0	2.10
ISO Factor Y1	2.15
ISO Factor Y2	3.20
Bearing Weight	kg
Cage Type	EJ
Cage Material	Steel



THE TIMKEN COMPANY

NORTH CANTON, OHIO USA

23140EJW33C3
SRB ASSEMBLY

Dynamic Radial Rating (Two Rows)	1660000	N
Static Radial Rating	2290000	N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY