



The Timken Company

4500 Mt Pleasant St. NW


N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number 23264KEMBW906AC3, Spherical Roller Bearings - Brass Cage

Spherical bearings are designed to manage high radial loads even when misalignment, poor lubrication, contamination, extreme speeds or critical application stresses are present.



[Specifications](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

Design Unit	Metric
d - Bore	320.000 mm
Bore_Taper	1/12
Cage Type	EMB
Cage Material	Brass
Superseded Part	23264KYMBW906AC3

Dimensions



D - Outer Diameter

580 mm
22.8350 in

B' - Inner Ring Width	208 mm 8.189 in
B - Outer Ring Width	208 mm 8.1890 in

Abutment and Fillet Dimensions

R - Inner Ring "To Clear" Radius¹	4 mm 0.160 in
r - Outer Ring "To Clear" Radius²	4 mm 0.16 in
da - Inner Ring Backing Diameter	377.000 mm 14.8000 in
Da - Outer Ring Backing Diameter	516.000 mm 20.300 in

Basic Load Ratings

C0 - Static Radial Rating	7090000 N 1590000 lbf
C1(2) - Dynamic Radial Rating (Two-Rows)	4770000 N 1070000 lbf

Factors

e - ISO Factor³	0.34
Y0 - ISO Factor⁴	1.93
Y1 - ISO Factor⁵	1.98
Y2 - ISO Factor⁶	2.94
Reference Thermal Speed Rating (Grease)	490 rpm

Reference Thermal Speed Rating (Oil)⁷	530 rpm
Cg - Geometry Factor⁸	0.1354

¹ Maximum housing fillet radius that bearing corners will clear.

² Maximum shaft fillet radius that bearing corners will clear.

³ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.


⁴ These factors apply for both inch and metric calculations. See engineering

⁵ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁶ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.


⁷ See thermal speed ratings in the engineering section.

⁸ Geometry constant for Lubrication Life Adjustment Factor a3l.



METRIC UNITS

Number of Rollers Per Row	20
ISO Factor e	0.34
ISO Factor Y0	1.93
ISO Factor Y1	1.98
ISO Factor Y2	2.94
Bearing Weight	245.1 kg
Cage Type	EMB
Cage Material	Brass
Bore Taper	1/12



THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

23264KEMBW906AC3 SRB ASSEMBLY		
Dynamic Radial Rating (Two Rows)	4770000	N
Static Radial Rating	7090000	N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY